

Safety Data Sheet

3C WOOD REPAIR RESIN COMPONENT A







Safety Data Sheet dated 16/02/2018, version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier
Trade name: 3C WOOD REPAIR RESIN COMPONENT A
Trade code: CCC0081
- 1.2. Relevant identified uses of the substance or mixture and uses advised against
Recommended use:
Epoxy filler
- 1.3. Details of the supplier of the safety data sheet
Supplier: County Construction Chemicals
Unit 4 Chingford Industrial Centre
Hall Lane
Chingford, London
E4 8DJ
England
T: 020 8524 1931 F: 020 8529 0103
E: info@countyconchem.co.uk
- 1.4. Emergency telephone number: 020 8524 1931

SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture
EC regulation criteria 1272/2008 (CLP)

-  Warning, Skin Irrit. 2, Causes skin irritation.
-  Danger, Eye Dam. 1, Causes serious eye damage.
-  Warning, Skin Sens. 1, May cause an allergic skin reaction.
-  Aquatic Chronic 2, Toxic to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:
No other hazards

- 2.2. Label elements
Hazard pictograms:



- Danger
Hazard statements:
H315 Causes skin irritation.
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.
- Precautionary statements:
P280 Wear protective gloves and eye/face protection.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P501 Dispose of contents/container in accordance with local regulations.
- Special Provisions:
EUH205 Contains epoxy constituents. May produce an allergic reaction.
- Contains
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700)
2-Propenoic acid, reaction products with pentaerythritol
1,6-Hexanediol diglycidyl ether
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[1,6-hexanediylbis(oxymethylene)]bis[oxirane]
- 2.3. Other hazards

Safety Data Sheet

3C WOOD REPAIR RESIN COMPONENT A

vPvB Substances: None - PBT Substances: None





























SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
>= 50% - < 65%	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700)	Index number: 603-074-00-8 CAS: 25068-38-6 EC: 500-033-5 REACH No.: 01-2119456619-26	 3.3/2 Eye Irrit. 2 H319  3.2/2 Skin Irrit. 2 H315  3.4.2/1-1A-1B Skin Sens. 1,1A,1B H317  4.1/C2 Aquatic Chronic 2 H411
>= 10% - < 12.5%	2-Propenoic acid, polymer with 2,2-bis(hydroxymethyl)-1,3-propanediol, methyloxirane and oxirane	CAS: 144086-02-2 EC: 604-394-0 REACH No.: 01-2119979050-40	 3.3/2 Eye Irrit. 2 H319  4.1/C2 Aquatic Chronic 2 H411
>= 7% - < 10%	1,6-Hexanediol diglycidyl ether	CAS: 16096-31-4 EC: 240-260-4	 3.3/2 Eye Irrit. 2 H319  3.2/2 Skin Irrit. 2 H315  3.4.2/1 Skin Sens. 1 H317  4.1/C3 Aquatic Chronic 3 H412
>= 3% - < 5%	2-Propenoic acid, reaction products with pentaerythritol	CAS: 1245638-61-2 EC: 629-850-6 REACH No.: 01-2119490003-49	 3.1/4/Oral Acute Tox. 4 H302  3.3/1 Eye Dam. 1 H318  3.2/2 Skin Irrit. 2 H315  3.4.2/1 Skin Sens. 1 H317  4.1/C2 Aquatic Chronic 2 H411
>= 1% - < 3%	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[1,6-hexanediylbis(oxymethylene)]bis[oxirane]	CAS: 356761-34-7	 3.2/2 Skin Irrit. 2 H315  3.3/2 Eye Irrit. 2 H319  3.4.2/1 Skin Sens. 1 H317  4.1/C3 Aquatic Chronic 3 H412
>= 0.5% - < 1%	hexane-1,6-diol diacrylate	Index number: 607-109-00-8 CAS: 13048-33-4 EC: 235-921-9 REACH No.: 01-2119484737-22	 3.3/2 Eye Irrit. 2 H319  3.2/2 Skin Irrit. 2 H315  3.4.2/1-1A-1B Skin Sens. 1,1A,1B H317
>= 0.1% - < 0.5%	pentaerythritol tetraacrylate	Index number: 607-122-00-9 CAS: 4986-89-4 EC: 225-644-1	 3.3/2 Eye Irrit. 2 H319  3.2/2 Skin Irrit. 2 H315  3.4.2/1-1A-1B Skin Sens. 1,1A,1B H317
>= 0.1% - < 0.5%	pentaerythritol triacrylate	Index number: 607-110-00-3 CAS: 3524-68-3 EC: 222-540-8	 3.3/2 Eye Irrit. 2 H319  3.2/2 Skin Irrit. 2 H315  3.4.2/1-1A-1B Skin Sens. 1,1A,1B H317

SECTION 4: First aid measures

4.1. Description of first aid measures

Safety Data Sheet

3C WOOD REPAIR RESIN COMPONENT A

In case of skin contact:

CONSULT A PHYSICIAN IMMEDIATELY.

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None known

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

CO₂, powder extinguisher, foam, water spray.

Extinguishing media which must not be used for safety reasons:

Water jet.

5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke.

Do not inhale explosion and/or combustion gases (carbon monoxide, carbon dioxide, oxides of nitrogen).

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Suitable material for collection: inert absorbent material (e.g. sand, vermiculite)

After the product has been recovered, rinse the area and materials involved.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

See chapter 10.5

Instructions as regards storage premises:

Keep container tightly closed in a cool, well-ventilated place, away from heat.

7.3. Specific end use(s)

See chapter 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No occupational exposure limit available

Safety Data Sheet

3C WOOD REPAIR RESIN COMPONENT A

DNEL Exposure Limit Values

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) - CAS: 25068-38-6

Worker Professional: 8.3 mg/kg - Consumer: 3.6 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects

Worker Professional: 12.3 mg/m3 - Consumer: 0.75 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Professional: 8.3 mg/kg - Consumer: 3.6 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Professional: 12.3 mg/m3 - Consumer: 0.75 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 0.75 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects

Consumer: 0.75 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

2-Propenoic acid, polymer with 2,2-bis(hydroxymethyl)-1,3-propanediol, methyloxirane and oxirane - CAS: 144086-02-2

Worker Professional: 5.87 mg/m3 - Consumer: 1.45 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Professional: 3.33 mg/kg - Consumer: 1.67 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Professional: 0.83 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) - CAS: 25068-38-6

Target: Fresh Water - Value: 0.006 mg/l

Target: Marine water - Value: 0.0006 mg/l

Target: Freshwater sediments - Value: 0.996 mg/kg

Target: Marine water sediments - Value: 0.0996 mg/kg

Target: Microorganisms in sewage treatments - Value: 10 mg/l

Target: Soil (agricultural) - Value: 0.196 mg/kg

2-Propenoic acid, polymer with 2,2-bis(hydroxymethyl)-1,3-propanediol, methyloxirane and oxirane - CAS: 144086-02-2

Target: Fresh Water - Value: 0.0079 mg/l

Target: Marine water - Value: 0.00079 mg/l

Target: Freshwater sediments - Value: 0.119 mg/kg

Target: Marine water sediments - Value: 0.0119 mg/kg

Target: Soil (agricultural) - Value: 0.0192 mg/kg

8.2. Exposure controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Eye protection:

Eye glasses with side protection (EN 166).

Skin protection:

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

Hands protection:

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

For prolonged or repeated handling, use chemical resistant gloves.

Suitable materials for safety gloves; EN 374:

NBR (nitrile rubber).

FKM (fluoro rubber).

The selection of suitable gloves does not only depend on the material, but also on other quality characteristics and varies from manufacturer to another one, and on the manner and times of use of the mixture.

Respiratory protection:

Combination filtering device (DIN EN 141).

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators.

Environmental exposure controls:

See chapter 6.2

Appropriate engineering controls:

See section 7.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes:
Appearance and colour:	colored thick paste	Internal method IPASVS - IPCOVS	--
Odour:	typical	--	Internal assessment
Odour threshold:	nd	--	--

Safety Data Sheet

3C WOOD REPAIR RESIN COMPONENT A

pH:	nd	--	--
Melting point / freezing point:	nd	--	--
Initial boiling point and boiling range:	nd	--	--
Flash point:	> 100 °C	--	Internal assessment
Evaporation rate:	nd	--	--
Solid/gas flammability:	nd	--	--
Upper/lower flammability or explosive limits:	nd	--	--
Vapour pressure:	nd	--	--
Vapour density:	nd	--	--
Relative density:	1.20 ± 0.02 kg/l	Internal method IPPSPC	--
Solubility in water:	not soluble	--	Internal assessment
Solubility in oil:	nd	--	--
Partition coefficient (n-octanol/water):	nd	--	--
Auto-ignition temperature:	nd	--	--
Decomposition temperature:	nd	--	--
Viscosity:	nd	--	--
Explosive properties:	na	--	--
Oxidizing properties:	na	--	--

9.2. Other information

Properties	Value	Method:	Notes:
Miscibility:	nd	--	--
Conductivity:	nd	--	--

Legend:

na = not applicable - nd = not available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

Because of heat or fire the preparation can release carbon oxides and vapours which may be harmful to health.

10.4. Conditions to avoid

Avoid to keep near heat sources.

10.5. Incompatible materials

Powerful oxidising agents, powerful reducing agents, aliphatic and aromatic amines.

See chapter 10.3

10.6. Hazardous decomposition products

No hazardous decomposition products when stored and handled correctly.

See chapter 5.2

SECTION 11: Toxicological information

11.1. Information on toxicological effects

There are no data available on the mixture itself.

Toxicological information of the main substances found in the product:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) - CAS: 25068-38-6

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg

Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg

2-Propenoic acid, polymer with 2,2-bis(hydroxymethyl)-1,3-propanediol, methyloxirane and oxirane - CAS: 144086-02-2

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg

1,6-Hexanediol diglycidyl ether - CAS: 16096-31-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat 8500 mg/kg

2-Propenoic acid, reaction products with pentaerythritol - CAS: 1245638-61-2

Safety Data Sheet

3C WOOD REPAIR RESIN COMPONENT A

- a) acute toxicity:
 - Test: LD50 - Route: Oral 540 mg/kg
 - Test: LD50 - Route: Skin 2000 mg/kg

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

SECTION 12: Ecological information

Adopt sound working practices, so that the product is not released into the environment.

12.1. Toxicity

Ecotoxicological studies of the product are not available.

Ecotoxicological information of the main substances found in the mixture:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) - CAS: 25068-38-6

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia 2.7 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish 1.5 mg/l - Duration h: 96

Endpoint: EC50 - Species: Algae 9.4 mg/l - Duration h: 72

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia 0.3 mg/l - Notes: 21d

2-Propenoic acid, polymer with 2,2-bis(hydroxymethyl)-1,3-propanediol, methyloxirane and oxirane - CAS: 144086-02-2

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish 7.9 mg/l - Duration h: 96

Endpoint: IC50 - Species: Algae > 100 mg/l - Duration h: 72

Endpoint: EC50 - Species: Daphnia 90.94 mg/l - Duration h: 48

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Algae 58.8 mg/l

1,6-Hexanediol diglycidyl ether - CAS: 16096-31-4

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish 17.1 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia 47 mg/l - Duration h: 48

2-Propenoic acid, reaction products with pentaerythritol - CAS: 1245638-61-2

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish 3.2 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia 13 mg/l - Duration h: 48

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Algae 10 mg/l

12.2. Persistence and degradability

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

None

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Do not allow to enter drains or water courses.

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information

Safety Data Sheet

3C WOOD REPAIR RESIN COMPONENT A



- 14.1. UN number
 ADR-UN Number: 3077
 IATA-UN Number: 3077
 IMDG-UN Number: 3077
- 14.2. UN proper shipping name
 ADR-Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700))
 IATA-Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700))
 IMDG-Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700))
- 14.3. Transport hazard class(es)
 ADR-Class: 9
 ADR - Hazard identification number: 90
 IATA-Class: 9
 IATA-Label: 9
 IMDG-Class: 9
- 14.4. Packing group
 ADR-Packing Group: III
 IATA-Packing Group: III
 IMDG-Packing Group: III
- 14.5. Environmental hazards
 ADR-Environmental Pollutant: Yes
 IMDG-Marine pollutant: Marine Pollutant
- 14.6. Special precautions for user
 ADR-Subsidiary risks: -
 ADR-S.P.: 274 335 375 601
 ADR-Transport category (Tunnel restriction code): 3 (E)
 IATA-Passenger Aircraft: 956
 IATA-Subsidiary risks: -
 IATA-Cargo Aircraft: 956
 IATA-S.P.: A97 A158 A179 A197
 IATA-ERG: 9L
 IMDG-EmS: F-A , S-F
 IMDG-Subsidiary risks: -
 IMDG-Stowage and handling: Category A SW23
 IMDG-Segregation: -
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code
 N.A.

SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
 Dir. 98/24/EC (Risks related to chemical agents at work)
 Dir. 2000/39/EC (Occupational exposure limit values)
 Regulation (EC) n. 1907/2006 (REACH)
 Regulation (EC) n. 1272/2008 (CLP)
 Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
 Regulation (EU) 2015/830
 Regulation (EU) n. 286/2011 (ATP 2 CLP)
 Regulation (EU) n. 618/2012 (ATP 3 CLP)
 Regulation (EU) n. 487/2013 (ATP 4 CLP)
 Regulation (EU) n. 944/2013 (ATP 5 CLP)
 Regulation (EU) n. 605/2014 (ATP 6 CLP)
 Regulation (EU) 2015/1221 (ATP 7 CLP)
- Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:
 Restrictions related to the product:
 No restriction.
 Restrictions related to the substances contained:
 No restriction.

Safety Data Sheet

3C WOOD REPAIR RESIN COMPONENT A

Volatile Organic compounds - VOCs = 0.30 %
Volatile CMR substances = 0.00 %

Where applicable, refer to the following Italian regulatory provisions :
Directive 2012/18/EU (Seveso III)
Directive 2010/75/EU
Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):
Seveso III category according to Annex 1, part 1
Product belongs to category: E2

15.2. Chemical safety assessment
No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Text of phrases referred to under heading 3:
H319 Causes serious eye irritation.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
H302 Harmful if swallowed.
H318 Causes serious eye damage.

Hazard class and hazard category	Code	Description
Acute Tox. 4	3.1/4/Oral	Acute toxicity (oral), Category 4
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Dam. 1	3.3/1	Serious eye damage, Category 1
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
Skin Sens. 1	3.4.2/1	Skin Sensitisation, Category 1
Skin Sens. 1,1A,1B	3.4.2/1-1A-1B	Skin Sensitisation, Category 1,1A,1B
Aquatic Chronic 2	4.1/C2	Chronic (long term) aquatic hazard, category 2
Aquatic Chronic 3	4.1/C3	Chronic (long term) aquatic hazard, category 3

Paragraphs modified from the previous revision:

SECTION 2: Hazards identification
SECTION 3: Composition/information on ingredients
SECTION 4: First aid measures
SECTION 7: Handling and storage
SECTION 8: Exposure controls/personal protection
SECTION 9: Physical and chemical properties
SECTION 11: Toxicological information
SECTION 12: Ecological information
SECTION 13: Disposal considerations
SECTION 14: Transport information
SECTION 15: Regulatory information
SECTION 16: Other information

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Skin Irrit. 2, H315	Calculation method
Eye Dam. 1, H318	Calculation method
Skin Sens. 1, H317	Calculation method
Aquatic Chronic 2, H411	Calculation method

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities
SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold
Safety data sheets of raw materials suppliers.

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

Safety Data Sheet

3C WOOD REPAIR RESIN COMPONENT A

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
WGK:	German Water Hazard Class.
N.A.	Not Applicable / Not Available