

WOOD REPAIR RESIN PRIMER



3C WOOD REPAIR RESIN PRIMER is a 2-part, impregnated, solvent free fluid based on epoxy resin with a mix ratio of 1:1. It has excellent adhesion to wood, stone and concrete and will penetrate deep into porous surfaces. It's used as a primer before applying 3C WOOD REPAIR EPOXY RESIN. It reinforces the wood fibre and prevents moisture penetration into the wood.

BENEFITS:

- Strengthens the fibres of the wood
- Penetrates quickly and deeply into the wood
- Gives a stronger bond of the epoxy repair to surface

INSTRUCTIONS:

- Please read before use
- Shake well before application
- Use guide on label for mixing ratio 1:1
- Mix both components in a mixing cup
- Make sure surface is dry & dust free
- Apply primer onto surface
- Leave 20 mins before applying 3C Wood Repair Resin
- Reseal cap after use

Processing Time	20 minutes (20°C)
Volume	200ml (two 100ml cartridges)
Packaging	6 sets per box
Colour	Transparent
Shelf Life	18 months from manufacturer date
Storage	+5°C & +50°C.

HEALTH & SAFETY:

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects. Avoid breathing vapours, mist or spray. Avoid release to environment. Wear protective gloves, protective clothing and eye protection. IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor. See MSDS for more information available from www.liquid-jacket.co.uk