Geocel the WORKS PRO Superior Construction Grab Adhesive

GCK0260

## SAFETY DATA SHEET

Not available.

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Geocel the WORKS PRO X Superior Construction Grab Adhesive

Product code : GCK0260

1.2 Relevant identified uses of the substance or mixture and uses advised against

Material uses : Sealants and adhesives

1.3 Details of the supplier of the safety data

sheet

Sherwin Williams Diversified Brands Limited

Western Wood Way Langage Science Park

Plympton Plymouth PL7 5BG

e-mail address of person

: technical@geocel.co.uk

responsible for this SDS

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : 111 (general public) and 0344 892 111 (Medical professional (NHS) only)

**Supplier** 

**Telephone number** : 01752 202060 (09:00 - 17:00)

## **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

**Product definition** : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Eye Irrit. 2, H319

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word : Warning

**Hazard statements**: Causes serious eye irritation.

**Precautionary statements** 

General : Read label before use. Keep out of reach of children. If medical advice is needed,

have product container or label at hand.

Date of issue/Date of revision :06, Feb, 2020. Date of previous issue :30, Sep, 2016. Version :1 1/12

Geocel the WORKS PRO Superior Construction Grab Adhesive

GCK0260

## **SECTION 2: Hazards identification**

**Prevention**: Wear eye or face protection. Wash hands thoroughly after handling.

**Response**: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

Storage: Not applicable.Disposal: Not applicable.

Hazardous ingredients : Aminopropyltrimethoxysilane

Supplemental label

elements

: Contains dioctylbis(pentane-2,4-dionato-O,O')tin. May produce an allergic reaction.

Annex XVII - Restrictions on the manufacture,

placing on the market and use of certain dangerous substances, mixtures and articles

: Not applicable.

**Special packaging requirements** 

Containers to be fitted with child-resistant

fastenings

: Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Other hazards which do

: None known.

not result in classification

## **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixture

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Туре
Aminopropyltrimethoxysilane	EC: 237-511-5 CAS: 13822-56-5	<3	Skin Irrit. 2, H315 Eye Dam. 1, H318	[1]
Organotin Compound	REACH #: 01-0000020199-67 EC: 483-270-6 CAS: 54068-28-9	<1	Skin Sens. 1, H317 STOT RE 2, H373	[1] [2]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

#### <u>Type</u>

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

Date of issue/Date of revision : 06, Feb, 2020. Date of previous issue : 30, Sep, 2016. Version : 1 2/12

Geocel the WORKS PRO Superior Construction Grab Adhesive

GCK0260

## **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

General: In all cases of doubt, or when symptoms persist, seek medical attention. Never give

anything by mouth to an unconscious person. If unconscious, place in recovery

position and seek medical advice.

**Eye contact**: Remove contact lenses, irrigate copiously with clean, fresh water, holding the

eyelids apart for at least 10 minutes and seek immediate medical advice.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

**Skin contact**: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognised skin cleanser. Do NOT use solvents or thinners.

If swallowed, seek medical advice immediately and show the container or label.

Keep person warm and at rest. Do NOT induce vomiting.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It

may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

#### 4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains dioctylbis(pentane-2,4-dionato-O,O')tin. May produce an allergic reaction.

## 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments** : No specific treatment.

See toxicological information (Section 11)

## **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing

ıg

: Recommended: alcohol-resistant foam, carbon dioxide, powders.

Unsuitable extinguishing

media

media

: Do not use water jet.

#### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

Hazardous combustion

products

: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Date of issue/Date of revision : 06, Feb, 2020. Date of previous issue : 30, Sep, 2016. Version : 1 3/12

Geocel the WORKS PRO Superior Construction Grab Adhesive

GCK0260

## **SECTION 5: Firefighting measures**

## 5.3 Advice for firefighters

Special protective actions for fire-fighters

: Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

Special protective equipment for fire-fighters

: Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.

Keep unnecessary and unprotected personnel from entering.

For emergency responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

: Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

## **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

# 7.1 Precautions for safe handling

: Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

Mixture may charge electrostatically: always use earthing leads when transferring from one container to another.

Operators should wear antistatic footwear and clothing and floors should be of the conducting type.

Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel.

Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws. Do not allow to enter drains or watercourses. **Information on fire and explosion protection** 

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

Date of issue/Date of revision : 06, Feb, 2020. Date of previous issue : 30, Sep, 2016. Version : 1 4/12

Geocel the WORKS PRO Superior Construction Grab Adhesive

GCK0260

## **SECTION 7: Handling and storage**

## 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully

resealed and kept upright to prevent leakage.

Contaminated absorbent material may pose the same hazard as the spilt product.

7.3 Specific end use(s)

Recommendations Industrial sector specific solutions

: Not available. : Not available.

Good housekeeping standards, regular safe removal of waste materials and regular maintenance of spray booth filters will minimise the risks of spontaneous combustion and other fire hazards.

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

## 8.1 Control parameters

## Occupational exposure limits

Product/ingredient name	Exposure limit values
	EH40/2005 WELs (United Kingdom (UK), 8/2018). Absorbed through skin.  STEL: 0.2 mg/m³, (as Sn) 15 minutes.  TWA: 0.1 mg/m³, (as Sn) 8 hours.

#### Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **DNELs/DMELs**

No DNELs/DMELs available.

#### **PNECs**

No PNECs available

#### 8.2 Exposure controls

## Appropriate engineering controls

- : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.
- : Users are advised to consider national Occupational Exposure Limits or other equivalent values.

Date of issue/Date of revision : 06, Feb, 2020. :30, Sep, 2016. Version : 1 Date of previous issue

Geocel the WORKS PRO Superior Construction Grab Adhesive

GCK0260

## SECTION 8: Exposure controls/personal protection

#### **Individual protection measures**

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection
Skin protection

Hand protection

: Use safety eyewear designed to protect against splash of liquids.

: Wear suitable gloves tested to EN374.

Gloves

: Short term exposure less than 10 minutes Continuous use Nitrile gloves. Hazardous ingredients Section 3 Short term exposure and For more than 4 hours of protection in the presence of Butanone Acetone or Methyl isobutyl ketone use Butyl gloves 0.7mm. For more than 4 hours of protection in the presence of Aromatic solvent Aliphatic solvent. or Mineral oil. use polyvinyl alcohol (PVA) gloves. The recommendation for the type or types of glove to use when handling this product is based on information from the following source: European Solvents Industry Group (ESIG).

Long Term Exposure Spill / For prolonged or repeated handling, use PE / PE Laminate gloves > 8 hours (breakthrough time).

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

**Body protection** 

- : Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres.
- : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Recommended: A2P2 (EN14387). Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Environmental exposure controls

: Do not allow to enter drains or watercourses.

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

Date of issue/Date of revision : 06, Feb, 2020. Date of previous issue : 30, Sep, 2016. Version : 1 6/12

GCK0260

## **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

**Appearance** 

Physical state : Liquid. [Paste.]

Colour : Various Odour : Sweetish.

Odour threshold : Not relevant/applicable due to nature of the product.

pН : Testing not technically possible.

Melting point/freezing point

Not relevant/applicable due to nature of the product.

Initial boiling point and

Not available.

boiling range

: Closed cup: >93.3°C Flash point Evaporation rate : Slower than Ether Phase

: Not relevant/applicable due to nature of the product. Flammability (solid, gas)

Upper/lower flammability or

explosive limits

Vapour pressure : Not Available (Not Tested).

Vapour density : Not relevant/applicable due to nature of the product.

Relative density : 1.743347741

Solubility(ies) Not relevant/applicable due to nature of the product. Solubility in water Not relevant/applicable due to nature of the product.

Partition coefficient: n-octanol/

water

Not relevant/applicable due to nature of the product.

Auto-ignition temperature : Not Available (Not Tested).

Decomposition temperature

Not relevant/applicable due to nature of the product.

: Not Available (Not Tested). Viscosity

Explosive properties : Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising properties : Under normal conditions of storage and use, hazardous reactions will not occur.

9.2 Other information **Aerosol product** 

Heat of combustion : 0.478 kJ/g

## SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : Stable under recommended storage and handling conditions (see Section 7).

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid When exposed to high temperatures may produce hazardous decomposition

products.

: Keep away from the following materials to prevent strong exothermic reactions: 10.5 Incompatible materials

oxidising agents, strong alkalis, strong acids.

10.6 Hazardous Decomposition products may include the following materials: carbon monoxide.

decomposition products carbon dioxide, smoke, oxides of nitrogen.

Date of issue/Date of revision : 06, Feb, 2020. 7/12 :30, Sep, 2016. Version: 1 Date of previous issue

Geocel the WORKS PRO Superior Construction Grab Adhesive

GCK0260

## **SECTION 10: Stability and reactivity**

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

## **SECTION 11: Toxicological information**

## 11.1 Information on toxicological effects

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains dioctylbis(pentane-2,4-dionato-O,O')tin. May produce an allergic reaction.

#### **Acute toxicity**

No data available

## **Acute toxicity estimates**

No data available

## Irritation/Corrosion

**Conclusion/Summary**: Not available.

**Sensitisation** 

**Conclusion/Summary**: Not available.

Mutagenicity

No data available

## **Carcinogenicity**

No data available

## Reproductive toxicity

No data available

#### **Teratogenicity**

No data available

## Specific target organ toxicity (single exposure)

No data available

#### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Organotin Compound	Category 2	Not determined	Not determined

#### **Aspiration hazard**

No data available

**Other information**: Not available.

Date of issue/Date of revision: 06, Feb, 2020.Date of previous issue: 30, Sep, 2016.Version: 18/12

Geocel the WORKS PRO Superior Construction Grab Adhesive

GCK0260

## **SECTION 12: Ecological information**

## 12.1 Toxicity

There are no data available on the mixture itself.

Do not allow to enter drains or watercourses.

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

## 12.2 Persistence and degradability

**Conclusion/Summary**: Not available.

#### 12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

**Mobility** : Not available.

#### 12.5 Results of PBT and vPvB assessment

PBT : Not applicable.vPvB : Not applicable.

12.6 Other adverse effects

: No known significant effects or critical hazards.

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains

and sewers.

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### **Product**

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

: Yes.

Disposal considerations

: Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no

longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

## European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances

## **Packaging**

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Date of issue/Date of revision : 06, Feb, 2020. Date of previous issue : 30, Sep, 2016. Version : 1 9/12

Geocel the WORKS PRO Superior Construction Grab Adhesive

GCK0260

Disposal considerations

Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

European waste catalogue (EWC) : Recycling possible. Ensure packaging is completely empty before recycling. Dispose of uncured residues in the same way as the product itself. Plastic articles 15 01 02 - metallic packaging 15 01 04 - mixed packaging 15 01 06. 15 01 10\* packaging containing residues of or contaminated by hazardous substances

Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## **SECTION 14: Transport information**

	ADR/RID	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport Hazard Class(es)/ Label(s)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.
Additional information	-	-	-

This mixture is not classified as dangerous according to international transport regulations (ADR/RID, IMDG, ICAO/IATA).

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code : Not applicable.

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

## SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Date of issue/Date of revision : 06, Feb, 2020. :30, Sep, 2016. Version : 1 10/12 Date of previous issue

Geocel the WORKS PRO Superior Construction Grab Adhesive

GCK0260

## SECTION 15: Regulatory information

Annex XVII - Restrictions : Not applicable.

on the manufacture. placing on the market and use of certain dangerous substances, mixtures and articles

#### Other EU regulations

#### **Seveso Directive**

This product is not controlled under the Seveso Directive.

15.2 Chemical safety

assessment

: No Chemical Safety Assessment has been carried out.

## **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and

: ATE = Acute Toxicity Estimate

acronyms

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

vPvB = Very Persistent and Very Bioaccumulative

Key literature references and sources for data

Date of printing

: Regulation (EC) No. 1272/2008 [CLP]

ADR = The European Agreement concerning the International Carriage of

Dangerous Goods by Road

DPD = Dangerous Preparations Directive [1999/45/EC] DSD = Dangerous Substances Directive [67/548/EEC]

IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by

Commission Regulation (EU) 2015/830

Directive 2012/18/EU, and relative amendments & additions Directive 2008/98/EC, and relative amendments & additions Directive 2009/161/EU, and relative amendments & additions

**CEPE Guidelines** 

: 06, Feb, 2020.

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classi	fication	Justification
Eye Irrit. 2, H319		Calculation method
Full text of abbreviated H statements	H317 May ca H318 Causes H319 Causes	s skin irritation. use an allergic skin reaction. s serious eye damage. s serious eye irritation. use damage to organs through prolonged or repeated re.
Full text of classifications [CLP/GHS]	: Eye Dam. 1, H318 Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT RE 2, H373	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITISATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2

Date of issue/Date of revision : 06, Feb, 2020. Date of previous issue : 30, Sep, 2016. Version : 1

Geocel the WORKS PRO Superior Construction Grab Adhesive

GCK0260

#### **SECTION 16: Other information**

Date of issue/ Date of

: 06, Feb, 2020.

revision

Date of previous issue : 30, Sep, 2016.

: If there is no previous validation date please contact your supplier for more

information.

Version : 1

## **Notice to reader**

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by Sherwin-Williams, including but not limited to the incorporation of non Sherwin-Williams products or the use or addition of products in proportions not specified by Sherwin-Williams. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country or local laws. The conditions for use of the product are not under the control of the manufacturer, therefore the customer/buyer/ user is responsible for determining the conditions necessary for the safe use of this product. The customer/ buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

Date of issue/Date of revision : 06, Feb, 2020. Date of previous issue : 30, Sep, 2016. Version : 1 12/12