GCK0259

General

SAFETY DATA SHEET

SECTION 1: Identificat	tion of the substance/mixture and of the company/undertaking		
1.1 Product identifier			
Product name	: FG_ Geocel theWORKS PRO Superior Construction Sealant & Adhesive (Colours)		
Product code	: GCK0259		
1.2 Relevant identified use	s of the substance or mixture and uses advised against		
Material uses	: Sealants and adhesives		
1.3 Details of the supplier sheet	of the safety data		
Sherwin Williams Diversifie Western Wood Way Langage Science Park Plympton Plymouth PL7 5BG	d Brands Limited Not available.		
e-mail address of person responsible for this SDS	: technical@geocel.co.uk		
1.4 Emergency telephone	number		
National advisory body/P	oison Centre		
Telephone number	: 111 (general public) and 0344 892 111 (Medical professional (NHS) only)		
<u>Supplier</u>			
Telephone number	: 01752 202060 (09:00 - 17:00)		
SECTION 2: Hazards i	dentification		
2.1 Classification of the su	ibstance or mixture		
Product definition	: Mixture		
Classification according Eye Irrit. 2, H319	to Regulation (EC) No. 1272/2008 [CLP/GHS]		
-	hazardous according to Regulation (EC) 1272/2008 as amended.		
•	ext of the H statements declared above.		
See Section 11 for more de	etailed information on health effects and symptoms.		
2.2 Label elements			
Hazard pictograms			
Signal word	: Warning		
Hazard statements	: Causes serious eye irritation.		

have product container or label at hand.

: Read label before use. Keep out of reach of children. If medical advice is needed,

GCK0259

SECTION 2: Hazards identification

Prevention	:	Wear eye or face protection. Wash hands thoroughly after handling.
Response	:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Storage	:	Not applicable.
Disposal	:	Not applicable.
Hazardous ingredients	:	Aminopropyltrimethoxysilane
Supplemental label elements	:	Contains dioctylbis(pentane-2,4-dionato-O,O')tin and Hydrocarbon Polymer. May produce an allergic reaction.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Special packaging requirem	en	<u>ts</u>
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.

2.3 Other hazards

Other hazards which do : None known. *not result in classification*

SECTION 3: Composition/information on ingredients

÷

3.2 Mixture

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Туре
Aminopropyltrimethoxysilane		<3	Skin Irrit. 2, H315	[1]
Organotin Compound	CAS: 13822-56-5 REACH #: 01-0000020199-67 EC: 483-270-6 CAS: 54068-28-9	<1	Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 2, H373	[1] [2]
Hydrocarbon Polymer	CAS: 71302-83-5	≤0.3	Skin Sens. 1, H317 Aquatic Chronic 3, H412	[1]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

[1] Substance classified with a health or environmental hazard

- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

GCK0259

SECTION 4: First aid measures

4.1 Description of first aid measures

General	 In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Eye contact	 Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	 Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	 If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains dioctylbis(pentane-2,4-dionato-O,O')tin, Hydrocarbon Polymer. May produce an allergic reaction.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	 In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.

See toxicological information (Section 11)

SECTION 5: Firefighting measures			
5.1 Extinguishing media			
Suitable extinguishing media	: Recommended: alcohol-resistant foam, carbon dioxide, powders.		
Unsuitable extinguishing media	: Do not use water jet.		

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture	 Fire will produce dense black smoke. Exposure to decomposition products cause a health hazard. 	s may
Hazardous combustion products	: Decomposition products may include the following materials: carbon mone carbon dioxide, smoke, oxides of nitrogen.	oxide,

Date of issue/Date of revision	:06, Feb, 2020.	Date of previous issue	:07, Jun, 2017.	Version : 1	3/12
--------------------------------	-----------------	------------------------	-----------------	-------------	------

GCK0259

SECTION 5: Firefighting measures

5.3 Advice for firefighters

Special protective actions for fire-fighters	:	Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.
Special protective equipment for fire-fighters	:	Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

SECTION 6: Accidental release measures

6.1	6.1 Personal precautions, protective equipment and emergency procedures				
	or non-emergency ersonnel	:	Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.		
			Keep unnecessary and unprotected personnel from entering.		
F	or emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".		
•	? Environmental ecautions	:	Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.		
for	Methods and material containment and eaning up	:	Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.		
	Reference to other ctions	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.		

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

	7.1 Precautions for safe handling	 Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or watercourses. Information on fire and explosion protection Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.
--	--------------------------------------	--

FG_ Geocel theWORKS PRO Superior Construction Sealant & Adhesive (Colours)

GCK0259

SECTION 7: Handling and storage

	5
7.2 Conditions for safe	: Store in accordance with local regulations.
storage, including any	Notes on joint storage
incompatibilities	Keep away from: oxidising agents, strong alkalis, strong acids.
-	Additional information on storage conditions
	Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.
	Contaminated absorbent material may pose the same hazard as the spilt product.
7.3 Specific end use(s)	
Recommendations	: Not available.
Industrial sector specific solutions	: Not available.

Good housekeeping standards, regular safe removal of waste materials and regular maintenance of spray booth filters will minimise the risks of spontaneous combustion and other fire hazards.

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingred	ient name		Exposure limit values			
Organotin Compound		EH40/2005 WELs (Un through skin. STEL: 0.2 mg/m³, (a TWA: 0.1 mg/m³, (a	s Sn) 15 minutes.		ed	
Recommended monitoring procedures	atmosphere of the ventila protective ex the following the assessm limit values a atmosphere of exposure (Workplace for the meas	et contains ingredients with or biological monitoring m ation or other control meas quipment. Reference show : European Standard EN thent of exposure by inhala and measurement strategy s - Guide for the application to chemical and biologica atmospheres - General re surement of chemical ager or methods for the determ	ay be required to sures and/or the n uld be made to mo 689 (Workplace a tion to chemical a y) European Stan on and use of proc l agents) Europea quirements for the nts) Reference to	determine the effecti ecessity to use respir ponitoring standards, s atmospheres - Guidal gents for comparison idard EN 14042 (Wor redures for the asses an Standard EN 482 e performance of pro- national guidance	ratory such as nce for n with rkplace sment cedures	
DNELs/DMELs						
No DNELs/DMELs availabl	e.					
<u>PNECs</u> No PNECs available						
8.2 Exposure controls						
Appropriate engineering controls	achieved by these are no vapours belo	quate ventilation. Where r the use of local exhaust v t sufficient to maintain cor ow the OEL, suitable respi	entilation and goo ncentrations of pa ratory protection r	d general extraction. rticulates and solvent nust be worn.	t	
	: Users are ac equivalent va	lvised to consider nationa alues.	I Occupational Ex	posure Limits or othe	۲	
Date of issue/Date of revision	:06, Feb, 2020.	Date of previous issue	:07, Jun, 2017.	Version :1	5/12	

GCK0259

SECTION 8: Exposure controls/personal protection

Individual protection measured	<u>ures</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Use safety eyewear designed to protect against splash of liquids.
Skin protection	
Hand protection	: Wear suitable gloves tested to EN374.
Gloves	: Short term exposure less than 10 minutes Continuous use Nitrile gloves. Hazardous ingredients Section 3 Short term exposure and For more than 4 hours of protection in the presence of Butanone Acetone or Methyl isobutyl ketone use Butyl gloves 0.7mm. For more than 4 hours of protection in the presence of Aromatic solvent Aliphatic solvent. or Mineral oil. use polyvinyl alcohol (PVA) gloves. The recommendation for the type or types of glove to use when handling this product is based on information from the following source: European Solvents Industry Group (ESIG).
	Long Term Exposure Spill / For prolonged or repeated handling, use PE / PE Laminate gloves > 8 hours (breakthrough time) .
	 There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Body protection	 Personnel should wear antistatic clothing made of natural fibres or of high- temperature-resistant synthetic fibres.
	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Recommended: A2P2 (EN14387). Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	Do not allow to enter drains or watercourses.

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

GCK0259

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties Appearance Physical state : Liquid. [Paste.] Colour : Various Odour : Odourless. Odour threshold : Not relevant/applicable due to nature of the product. pН : Testing not technically possible. Melting point/freezing point Not relevant/applicable due to nature of the product. Initial boiling point and Not available. boiling range : Closed cup: >93.3°C Flash point Evaporation rate : Slower than Ether Phase : Not relevant/applicable due to nature of the product. Flammability (solid, gas) Upper/lower flammability or 2 explosive limits Vapour pressure : Not Available (Not Tested). Vapour density : Not relevant/applicable due to nature of the product. Relative density : 1.576579573 Solubility(ies) Not relevant/applicable due to nature of the product. Solubility in water Not relevant/applicable due to nature of the product. Partition coefficient: n-octanol/ Not relevant/applicable due to nature of the product. water Auto-ignition temperature : Not Available (Not Tested). Decomposition temperature Not relevant/applicable due to nature of the product. : Kinematic (40°C): >0.205 cm²/s Viscosity : Under normal conditions of storage and use, hazardous reactions will not occur. Explosive properties : Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising properties 9.2 Other information Aerosol product Heat of combustion : 0.841 kJ/g SECTION 10: Stability and reactivity : No specific test data related to reactivity available for this product or its ingredients. 10.1 Reactivity : Stable under recommended storage and handling conditions (see Section 7). 10.2 Chemical stability 10.3 Possibility of : Under normal conditions of storage and use, hazardous reactions will not occur. hazardous reactions 10.4 Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products. : Keep away from the following materials to prevent strong exothermic reactions: 10.5 Incompatible materials oxidising agents, strong alkalis, strong acids. 10.6 Hazardous 5 Decomposition products may include the following materials: carbon monoxide, decomposition products carbon dioxide, smoke, oxides of nitrogen.

Date of issue/Date of revision	:06, Feb, 2020.	Date of previous issue	: 07, Jun, 2017.	Version : 1	7/12
	,,		, ,		

FG_ Geocel theWORKS PRO Superior Construction Sealant & Adhesive (Colours)

GCK0259

SECTION 10: Stability and reactivity

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains dioctylbis(pentane-2,4-dionato-O,O')tin, Hydrocarbon Polymer. May produce an allergic reaction.

Acute toxicity

No data available

Acute toxicity estimates

No data available

Irritation/Corrosion

Conclusion/Summary	: Not available.
Sensitisation	
Conclusion/Summary	: Not available.
<u>Mutagenicity</u>	

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Teratogenicity

No data available

Specific target organ toxicity (single exposure)

No data available

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Organotin Compound	Category 2	Not determined	Not determined

Aspiration hazard

No data available

Other information

: Not available.

FG_ Geocel theWORKS PRO Superior Construction Sealant & Adhesive (Colours)

GCK0259

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself. Do not allow to enter drains or watercourses.

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil	
Soil/water partition coefficient (K _{oc})	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

PBT	: Not applicable.
-----	-------------------

vPvB : Not applicable.

12.6 Other adverse effects	: No known significant effects or critical hazards.
	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.
SECTION 13: Disposal o	considerations

SECTION 13: Disposal considerations

13.1 Waste treatment method	ds	
<u>Product</u>		
Methods of disposal	:	The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	:	Yes.
Disposal considerations	:	Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation	
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	
Deekeeine		

Packaging

Methods of disposal

 The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

FG_ Geocel theWORKS PRO Superior Construction Sealant & Adhesive (Colours)			
GCK0259			
Disposal considerations	: Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.		
European waste catalogue (EWC)	 Recycling possible. Ensure packaging is completely empty before recycling. Dispose of uncured residues in the same way as the product itself. Plastic articles 15 01 02 - metallic packaging 15 01 04 - mixed packaging 15 01 06. 15 01 10* packaging containing residues of or contaminated by hazardous substances 		
Special precautions	This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.		

SECTION 14: Transport information

	ADR/RID	IMDG	ΙΑΤΑ			
14.1 UN number	Not regulated.	Not regulated.	Not regulated.			
14.2 UN proper shipping name	-	-	-			
14.3 Transport Hazard Class(es)/ Label(s)	-	-	-			
14.4 Packing group	-	-	-			
14.5 Environmental hazards	No.	No.	No.			
Additional information	-	-	-			

This mixture is not classified as dangerous according to international transport regulations (ADR/RID, IMDG, ICAO/IATA).

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk	: Not applicable
according to Annex II of	
Marpol and the IBC Code	

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

GCK0259

SECTION 15: Regulatory information

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other EU regulations

Seveso Directive

This product is not controlled under the Seveso Directive.

15.2 Chemical safety	:	No Chemical Safety Assessment has be
----------------------	---	--------------------------------------

assessment

en carried out.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number vPvB = Very Persistent and Very Bioaccumulative
Key literature references and sources for data	 Regulation (EC) No. 1272/2008 [CLP] ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road DPD = Dangerous Preparations Directive [1999/45/EC] DSD = Dangerous Substances Directive [67/548/EEC] IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2015/830 Directive 2012/18/EU, and relative amendments & additions Directive 2008/98/EC, and relative amendments & additions Directive 2009/161/EU, and relative amendments & additions CEPE Guidelines

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Clas	sification	Justification
Eye Irrit. 2, H319		Calculation method
Full text of abbreviated H statements	H317 Ma H318 Ca H319 Ca H373 Ma exp	uses skin irritation. y cause an allergic skin reaction. uses serious eye damage. uses serious eye irritation. y cause damage to organs through prolonged or repeated osure. mful to aquatic life with long lasting effects.
Full text of classifications [CLP/GHS]	: Aquatic Chronic 3, H Eye Dam. 1, H318 Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT RE 2, H373	 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITISATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY - REPEATED
Date of issue/Date of revision	:06, Feb, 2020. Dat	e of previous issue : 07, Jun, 2017. Version : 1 11/12

GCK0259

SECTION 16: Other information

	EXPOSURE - Category 2
Date of printing	: 06, Feb, 2020.
Date of issue/ Date of revision	: 06, Feb, 2020.
Date of previous issue	: 07, Jun, 2017.
	 If there is no previous validation date please contact your supplier for more information.
Version	: 1

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by Sherwin-Williams, including but not limited to the incorporation of non Sherwin-Williams products or the use or addition of products in proportions not specified by Sherwin-Williams. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country or local laws. The conditions for use of the product are not under the control of the manufacturer, therefore the customer/buyer/ user is responsible for determining the conditions necessary for the safe use of this product. The customer/ buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.