

## TECHNICAL DATA

# Geocel® Trade Mate Lead & Gutter

## Silicone Sealant



**Geocel® Trade Mate Lead & Gutter** is a silicone rubber sealant for the installation and maintenance of gutter systems and downpipes, and for pointing joints between lead flashing and brickwork, masonry and stonework.

It is a high performance sealant that gives excellent adhesion to most common guttering systems including plastics, metals, painted surfaces and PVC-U.

**Geocel® Trade Mate Lead & Gutter** has a high joint movement capability and will give a totally water resistant seal.

- No primer needed
- High movement capability
- Will not crack, shrink or craze
- Remains permanently flexible
- Weather resistant
- Maintenance free
- Long service life

### PACKAGING

**Geocel® Trade Mate Lead & Gutter** is available in 310ml cartridges packed in boxes of 12.

### LIMITATIONS

**Geocel® Trade Mate Lead & Gutter** should not be applied to building material that bleed oils, plasticisers, or solvents. Mis-applied material can be removed when uncured using white spirit. Cured material can be removed using Geocel Silicone Sealant remover. It is advisable not to apply sealant in wet conditions or if rain is imminent.

### HEALTH AND SAFETY

Health and Safety data sheets available on request.

### STORAGE LIFE

12 Months from date of manufacture when stored in unopened original packaging at room temperature.



### TECHNICAL SERVICE

For further technical information, advice on suitability for specific applications, or detailed Health and Safety information, contact **Geocel®** Technical Service.

**IMPORTANT NOTE** The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Geocel's products are safe, effective and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Geocel's sole warranty is that the product will meet the Geocel sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

Geocel specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability.

Geocel disclaims liability for any incidental or consequential damages.