

CI/SfB				
CAW				
Uniclass				

### Description

ME317 is a reinforced kraft paper with modified acrylate dispersion, solvent-free adhesive.

### Colour

Yellow

### Packaging

Item No.	Roll Length	Roll Width	Rolls/Box
398631	40 m	60 mm	8

### Technical Information

Property	Test Method	Result
Material		Kraft paper with PE coating and solvent free acrylic dispersion adhesive
Bonding Strength*	DIN EN 1939	Approx. 35 N/25 mm
Compatibility with Common Building Materials		Given
Service Temperature		-40°C to +100°C
Application Temperature**		+5°C to +40°C
Storage		Store in shaded, dry conditions
Shelf Life		1 year when stored as recommended in original unopened packaging

\* depending on ambient temperature and relative humidity

\*\* depending on ambient temperature the use of appropriate illbruck primer is recommended

### Application

- Surfaces must be dry and free of oil, grease, dust and other anti-adhesive components. Bonding to frozen surfaces is not possible. The substrate must offer sufficient load-bearing capacity. On porous or damp substrates or at low temperatures, the use of primer ME904 is recommended.
- Detach the release paper and place the tape centrally over the joint (e.g. edge of overlapping membrane, or across a panel joint) so that the minimum coverage onto each substrate is 20 mm.
- Gradually peel off the release paper and adhere the tape whilst keeping it tension-free and wrinkle-free.
- To consolidate the bond apply firm pressure manually. Use of a seam roller will further improve the adhesion in most applications.

### Health & Safety Precautions

Safety data sheet must be read and understood before use.



## ME317

### Internal Membrane Tape

#### Usage / Purpose

Single-sided adhesive reinforced paper tape. For the airtight bonding of overlaps with ME003 vapour barrier membrane, used internally. Also for joints in OSB boards and as an air-seal tape for penetrations.

#### Key Benefits

- Fully compatible with all internal illbruck building protection products
- Strong kraft paper
- Easy to tear off by hand
- Quick and easy application

**ME317**

## Internal Membrane Tape



### Technical Service

tremco CPG UK Ltd has a team of experienced Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer Services on 01942 251400.

### Guarantee / Warranty

tremco CPG UK Ltd products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with tremco

CPG UK Ltd written instructions and (b) in any application recommended by tremco CPG UK Ltd, but which is proved to be defective, will be replaced free of charge.

No liability can be accepted for the information provided in this leaflet although it is published in good faith and believed to be correct. tremco CPG UK Ltd Limited reserves the right to alter product specifications without prior notice, in line with Company policy of continuous development and improvement.



**Tremco CPG UK Limited**  
Coupland Road  
Hindley Green, Wigan WN2 4HT  
United Kingdom  
T: +44 1942 251400  
F: +44 1942 251410

info.uk@tremcocpg.com  
www.tremcocpg.eu