

TF448

HIGH PERFORMANCE CCS TAPE



KEY BENEFITS SUMMARY

- Strong initial tack and permanent bond
- Enhanced plasticiser resistance
- Very low emission
- No waste
- Speed up installations
- Suitable for installations involving underfloor heating



PRODUCT INFORMATION

Description

TF448 is a tear resistant, very aggressive-grab double sided bonding tape.

Usage / Purpose

TF448 has been specially developed for the bonding of skirtings, cappings and cove formers used in the installation of commercial floor coverings. Bonds to almost all construction materials.

Colour

Amber

Packaging

TAPE WIDTH	ROLL LENGTH	ROLLS/ CARTON
20 mm	50 m	10 rolls
50 mm	50 m	5 rolls
85 mm	50 m	3 rolls

Standards

All aspects of the installation must be in accordance with the requirements of BS 8204, BS 8203 (Installation of Resilient Floor Coverings) or BS 5325 (Installation of Textile Floor Coverings) and supplementary specifications.

Preparation

- Site conditions must comply with British Standards CP 102, BS 8203, BS 5325 and supplementary specifications.
- The surfaces must be sound, clean, dry and free from oil, grease, paint, excessive dust and other contaminants liable to impair adhesion.
- Concrete and sand/cement screeds must be completely free from laitance.
- PVC should be conditioned in the environment in which it is being installed for a minimum of 24 hours.

Priming

- Dusty or very porous substrates should be sealed with CS150 (water based).

Application

- Apply TF448 to the component part(s) to be bonded. Remove the release liner and fix to the wall first and the press down firmly to create an instant bond.

Cleaning

No cleaning required.

Health & Safety Precautions

Safety data sheet must be read and understood before use.

Availability

Direct from Tremco CPG UK Limited (see bottom of leaflet for address and telephone details).

Technical Service

Tremco CPG UK Limited has a team of experienced Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer Services on 01942 251400.

Guarantee / Warranty

Tremco CPG UK Limited products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with Tremco CPG UK Limited written instructions and (b) in any application recommended by Tremco CPG UK Limited, but which is proved to be defective, will be replaced free of charge.

No liability can be accepted for the information provided in this leaflet although it is published in good faith and believed to be correct.

Tremco CPG UK Limited Limited reserves the right to alter product specifications without prior notice, in line with Company policy of continuous development and improvement.

TF448

HIGH PERFORMANCE CCS TAPE



TECHNICAL DATA

PROPERTY	RESULT
Composition	Tear resistant PES/PVA non-crimp fabric tape with a nominal 220 g/m ² special coating
Open Time/Workability (at +20°C)	Once release paper is removed apply immediately to substrates
Nominal Thickness	0.22 mm
Coverage	50 m rolls
Application Temperature Range (Substrate)	+15° to +30°C
Service Temperature Range	-20°C to +70°C
Storage	Store in shaded dry conditions between +5°C and +30°C - DO NOT ALLOW TO FREEZE
Shelf Life	12 months from manufacture date when stored as recommended in original unopened containers



Tremco CPG UK Limited - A Company approved to:

Tremco CPG UK Limited
Coupland Rd, Hindley Green, Wigan WN2 4HT
United Kingdom
Tel: +44 (0)1942 251400
Email: hello@tremcocpg.com



2021-03