

Metolux®

**PRE-MIX**

**STYRENE FREE  
2 pt WOOD FILLER**

LOW ODOUR STYRENE-FREE FORMULA



WHITE

NATURAL

# Product Data Sheet

## Description

Metolux 2 Part Pre-Mix Wood Filler is an innovative two-part high strength wood filler designed to guarantee the proper ratio mix of hardener and resin to provide the strongest repair possible to wood imperfections.


## Key Benefits and applications

For use with any silicone/sealant tool

- Single unit packaging available in WHITE or NATURAL colour
- Guaranteed ratio hardener/resin mix
- Used with a standard silicone tool and a putty knife, or mixer nozzle option
- Strength of a 2 part mix with the ease of a 1 part filler
- No need for separate hardener tubes
- Weatherproof
- Re-use many times
- Low Odour

## Gel and Cure Times

Temperature	Gel	Cure
5	10.00	35.00
15	4.35	22.00
25	2.00	13.00



## Product Codes

Code	Product	Qty
	<b>White</b>	
65420	Pre Mix 300g Plain Box without mixers	15pcs
	<b>Natural</b>	
65419	Pre Mix 300g Plain Box without mixers	15pcs
	<b>Ancillaries</b>	
65372	Spare Mixers Bag Short with Hanger	10pcs
65463	Chemfix Silicone Extrusion Tool	12pcs

This product should be stored between +5°C & +25°C. Avoid Direct Sunlight The Shelf life of the product is 18 months from the manufacture date.

The information and data given is based on our own experience, research and testing and is believed to be reliable and accurate. However, as Chemfix Products cannot know the varied uses to which its products may be applied, or the methods of application used, no warranty as to the fitness or suitability of its products is given or implied. It is the users responsibility to determine suitability of use. For further information please contact our Technical department.

**Metolux®**

# PRE-MIX

## STYRENE FREE 2 pt WOOD FILLER

LOW ODOUR STYRENE-FREE FORMULA



### Repairs Types

#### Manual Mixing



#### Or with Mixer



**Use with any  
high quality  
silicone tool**

### Repair Instructions



1. To ensure proper adhesion the surface must be dry, clean and free from dust oil and grease.
2. Mixing will start the curing process therefore prepare only what can be used immediately.
3. Apply using a spatula or a putty knife leaving the filler slightly "proud" of the surface to allow for sanding.
4. Quick and easy sanding is achieved if the filler is sanded down within 15-30 minutes from mixing and application.
5. The final repair is ready for coating

**chemfix**  
TOTAL SERVICE

Manufactured by Chemfix Products Ltd in the UK