

OB41 Fast Tack Contact Adhesive Spray  
Date: 15.04.2024

Replaces: N/A  
Ref: 0634.0.AFT/DL

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product Name OB41 Fast Tack Contact Adhesive Spray  
Pure substance/mixture Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesive  
Uses advised against None known

### 1.3. Details of the supplier of the safety data sheet

#### Company Name

Siroflex Limited  
Dodworth Business Park  
Dodworth, Barnsley  
South Yorkshire, S75 3SP  
Tel +44 (0)1226 771600

Further information available from: [www.ob1original.com](http://www.ob1original.com)

### 1.4. Emergency telephone number

United Kingdom + 44 (0) 1226 771600 (Office Hours Only)  
Ireland **NPIC - National Poison Information Centre**  
Members of the Public: +353 (01) 8092166 (8.00 am to 10.00 pm - 7 days a week)  
Europe Healthcare Professionals: +353 (01) 8092566 (24 hour service)  
112

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aspiration hazard	Category 1 - (H304)
Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Specific target organ toxicity — single exposure	Category 3 - (H336)
Category 3 Narcotic effects	
Chronic aquatic toxicity	Category 2 - (H411)
Aerosols	Category 1 - (H222, H229)

### 2.2. Label elements

Contains Acetone, Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics, Hydrocarbons, C6, isoalkanes, <5% n-hexane

# SAFETY DATA SHEET

OB41 Fast Tack Contact Adhesive Spray  
Date: 15.04.2024

Replaces: N/A  
Ref: 0634.0.AFT/DL



**Signal word**  
Danger

## Hazard statements

H304 - May be fatal if swallowed and enters airways.  
H315 - Causes skin irritation.  
H319 - Causes serious eye irritation.  
H336 - May cause drowsiness or dizziness.  
H411 - Toxic to aquatic life with long lasting effects.  
H222 - Extremely flammable aerosol.  
H229 - Pressurised container: May burst if heated.

## Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand  
P102 - Keep out of reach of children  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P211 - Do not spray on an open flame or other ignition source  
P251 - Do not pierce or burn, even after use  
P261 - Avoid breathing vapours  
P273 - Avoid release to the environment  
P280 - Wear protective gloves and eye/face protection  
P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor  
P302 + P352 - IF ON SKIN: Wash with plenty of water and soap  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P331 - Do NOT induce vomiting  
P391 - Collect spillage  
P405 - Store locked up  
P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F  
P501 - Dispose of contents/ container to an approved waste disposal plant

## Additional information

This product is exempt from the requirement for a child resistant fastening and tactile warning of danger, as it is an aspiration hazard, placed on the market in the form of an aerosol or in a container with a sealed spray attachment.

## 2.3. Other hazards

In case of insufficient ventilation and/or through use, the formation of a explosive/highly flammable mixture is possible. Harmful to aquatic life.

## PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	EC No (EU)	CAS No	Weight-%	Classification	Specific	REACH
---------------	------------	--------	----------	----------------	----------	-------

# SAFETY DATA SHEET

OB41 Fast Tack Contact Adhesive Spray  
Date: 15.04.2024

Replaces: N/A  
Ref: 0634.0.AFT/DL

	Index No)			according to Regulation (EC) No. 1272/2008 [CLP]	concentration limit (SCL)	registration number
Petroleum gases, liquefied <0.1% w/w 1,3 Butadiene	(649-202-00-6) 270-704-2	68476-85-7	40 - <80	Flam. Gas 1 (H220) Press. Gas (H280)	-	-
Acetone	(606-001-00-8) 200-662-2	67-64-1	>25 - <40	Eye Irrit. 2 (H319) (EUH066) STOT SE 3 (H336) Flam. Liq. 2 (H225)	-	01-2119471330-49-XXXX
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	64742-49-0	10 - <20	STOT SE 3 (H336) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Aquatic Chronic 2 (H411) Flam. Liq. 2 (H225)	-	01-2119475515-33-xxxx
Hydrocarbons, C6, isoalkanes, <5% n-hexane	931-254-9	64742-49-0	10 - <20	STOT SE 3 (H336) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Aquatic Chronic 2 (H411) Flam Liq. 2 (H225) (EUH066)	-	01-2119484651-34-XXXX

## Full text of H- and EUH-phrases: see section 16

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## Notes

See section 16 for more information

Chemical name	Notes
Petroleum gases, liquefied <0.1% w/w 1,3 Butadiene - 68476-85-7	K,S,U
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics - 64742-49-0	P
Hydrocarbons, C6, isoalkanes, <5% n-hexane - 64742-49-0	P

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General advice

Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

# SAFETY DATA SHEET

OB41 Fast Tack Contact Adhesive Spray  
Date: 15.04.2024

Replaces: N/A  
Ref: 0634.0.AFT/DL

<b>Inhalation</b>	Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical attention. Delayed pulmonary edema may occur.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Get immediate medical attention.
<b>Self-protection of the first aider</b>	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

## 4.2. Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	Difficulty in breathing. Coughing and/ or wheezing. Dizziness. May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
-----------------	--

## 4.3. Indication of any immediate medical attention and special treatment needed

<b>Note to doctors</b>	Because of the danger of aspiration, emesis or gastric lavage should not be used unless the risk is justified by the presence of additional toxic substances.
------------------------	---

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

<b>Suitable Extinguishing Media</b>	Dry chemical. Carbon dioxide (CO <sub>2</sub> ). Water spray.
<b>Unsuitable extinguishing media</b>	DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

### 5.2. Special hazards arising from the substance or mixture

<b>Specific hazards arising from the chemical</b>	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated.
<b>Hazardous combustion products</b>	Carbon oxides. Carbon monoxide. Carbon dioxide (CO <sub>2</sub> ).

### 5.3. Advice for firefighters

<b>Special protective equipment and precautions for fire-fighters</b>	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.
---	--

## **SECTION 6: Accidental release measures**

# SAFETY DATA SHEET

OB41 Fast Tack Contact Adhesive Spray  
Date: 15.04.2024

Replaces: N/A  
Ref: 0634.0.AFT/DL

## 6.1. Personal precautions, protective equipment and emergency procedures

<b>Personal precautions</b>	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Avoid breathing dust/fume/gas/mist/vapours/spray.
<b>Other information</b>	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.
<b>For emergency responders</b>	Use personal protection recommended in Section 8.

## 6.2. Environmental precautions

<b>Environmental precautions</b>	Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.
----------------------------------	--

## 6.3. Methods and material for containment and cleaning up

<b>Methods for containment</b>	Keep out of drains, sewers, ditches and waterways. Stop leak if you can do it without risk. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Flood with water to complete polymerization and scrape off floor.
<b>Methods for cleaning up</b>	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.
<b>Prevention of secondary hazards</b>	Clean contaminated objects and areas thoroughly observing environmental regulations.

## 6.4. Reference to other sections

<b>Reference to other sections</b>	See section 8 for more information. See section 13 for more information.
------------------------------------	--

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

<b>Advice on safe handling</b>	Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapours or mists. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.
<b>General hygiene considerations</b>	Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

### 7.2. Conditions for safe storage, including any incompatibilities

<b>Storage Conditions</b>	Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store in a cool, dry area away from potential sources
---------------------------	--

# SAFETY DATA SHEET

OB41 Fast Tack Contact Adhesive Spray  
Date: 15.04.2024

Replaces: N/A  
Ref: 0634.0.AFT/DL

of heat, open flames, sunlight or other chemicals. Store locked up. Keep out of the reach of children. Store away from other materials. Keep/store only in original container. Store in a dry place. Store in a closed container.

## 7.3. Specific end use(s)

**Specific use(s)**  
Adhesive.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure Limits

Chemical name	European Union	United Kingdom
Petroleum gases, liquefied <0.1% w/w 1,3 Butadiene 68476-85-7	-	TWA: 1000 ppm TWA: 1750 mg/m <sup>3</sup> STEL: 1250 ppm STEL: 2180 mg/m <sup>3</sup>
Acetone 67-64-1	TWA: 500 ppm TWA: 1210 mg/m <sup>3</sup>	TWA: 500 ppm TWA: 1210 mg/m <sup>3</sup> STEL: 1500 ppm STEL: 3620 mg/m <sup>3</sup>

Chemical name	European Union	Ireland	United Kingdom
Acetone 67-64-1	-	50 mg/L (urine - Acetone end of shift)	-

**Derived No Effect Level (DNEL)** No information available

Derived No Effect Level (DNEL)			
Acetone (67-64-1)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Dermal	186 mg/kg bw/d	
Short term Local health effects worker	Inhalation	2420 mg/m <sup>3</sup>	
Long term Systemic health effects worker	Inhalation	1210 mg/m <sup>3</sup>	

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	2085 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	300 mg/kg bw/d	

Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor

# SAFETY DATA SHEET

OB41 Fast Tack Contact Adhesive Spray  
Date: 15.04.2024

Replaces: N/A  
Ref: 0634.0.AFT/DL

worker Systemic health effects Long term	Dermal	13964 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	2085 mg/m <sup>3</sup>	

Derived No Effect Level (DNEL)			
Acetone (67-64-1)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	200 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	62 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	62 mg/kg bw/d	

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	447 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	149 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	149 mg/kg bw/d	

## Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)	
Acetone (67-64-1)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	10.6 mg/l
Freshwater - intermittent	21 mg/l
Marine water	1.06 mg/l
Microorganisms in sewage treatment	100 mg/l
Freshwater sediment	30.4 mg/kg dry weight
Marine water	3.04 mg/kg dry weight
Soil	29.5 mg/kg dry weight

## 8.2. Exposure controls

### Engineering controls

Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be exhausted directly at the point of origin.

### Personal protective equipment

#### Eye/face protection

Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.

#### Hand protection

Wear suitable gloves. Glove thickness > 0.7mm. Butyl rubber. Nitrile rubber. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove

# SAFETY DATA SHEET

OB41 Fast Tack Contact Adhesive Spray  
Date: 15.04.2024

Replaces: N/A  
Ref: 0634.0.AFT/DL

<b>Skin and body protection</b>	supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374
<b>Respiratory protection</b>	Wear appropriate personal protective clothing to prevent skin contact. Ensure adequate respiratory protection during spray applications. In case of insufficient ventilation, wear suitable respiratory equipment.
<b>Recommended filter type:</b>	Organic gases and vapours filter conforming to EN 14387. Wear a respirator conforming to EN 140 with Type A filter or better.

**Environmental exposure controls** No information available.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Liquid
<b>Appearance</b>	Aerosol
<b>Colour</b>	No information available
<b>Odour</b>	No information available.
<b>Odour threshold</b>	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
<b>Melting point / freezing point</b>	No data available	None known
<b>Initial boiling point and boiling range</b>	Not applicable, Aerosol	Not applicable, Aerosol
<b>Flammability</b>	Not applicable for liquids	None known
<b>Flammability Limit in Air</b>		None known
<b>Upper flammability or explosive limits</b>	No data available	
<b>Lower flammability or explosive limits</b>	No data available	
<b>Flash point</b>	Not applicable, Aerosol	Not applicable, Aerosol
<b>Autoignition temperature</b>	No data available	None known
<b>Decomposition temperature</b>		None known
<b>pH</b>	No data available	Not applicable. Insoluble in water.
<b>pH (as aqueous solution)</b>	No data available	None known
<b>Kinematic viscosity</b>	No data available	None known
<b>Dynamic viscosity</b>	No data available	
<b>Water solubility</b>	Slightly soluble.	None known
<b>Solubility(ies)</b>	No data available	None known
<b>Partition coefficient</b>	No data available	None known
<b>Vapour pressure</b>	No data available	None known
<b>Relative density</b>	0.71	None known
<b>Bulk Density</b>	No data available	
<b>Density</b>	No data available	
<b>Relative vapour density</b>	No data available	None known
<b>Particle characteristics</b>		
<b>Particle Size</b>	No information available	
<b>Particle Size Distribution</b>	No information available	

### 9.2. Other information

<b>Solid content (%)</b>	No information available	
<b>VOC content</b>		No data available

9.2.1. Information with regards to physical hazard classes  
Not applicable

9.2.2. Other safety characteristics  
No information available

## SECTION 10: Stability and reactivity



# SAFETY DATA SHEET

OB41 Fast Tack Contact Adhesive Spray  
Date: 15.04.2024

Replaces: N/A  
Ref: 0634.0.AFT/DL

## 10.1. Reactivity

Reactivity No information available.

## 10.2. Chemical stability

Stability Stable under normal conditions.

### Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

## 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Heating causes rise in pressure with risk of bursting.

## 10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks. Keep away from open flames, hot surfaces and sources of ignition. Extremes of temperature and direct sunlight.

## 10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents. Incompatible with oxidising agents.

## 10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

## **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Information on likely routes of exposure

##### Product Information

**Inhalation** Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. May cause drowsiness or dizziness.

**Eye contact** Specific test data for the substance or mixture is not available. May cause irritation. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.

**Skin contact** Repeated exposure may cause skin dryness or cracking. Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).

**Ingestion** Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Redness. May cause redness and tearing of the eyes. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

# SAFETY DATA SHEET

OB41 Fast Tack Contact Adhesive Spray  
Date: 15.04.2024

Replaces: N/A  
Ref: 0634.0.AFT/DL

## Acute toxicity

### Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	99,999.00 mg/kg
ATEmix (dermal)	99,999.00 mg/kg
ATEmix (inhalation-gas)	99,999.00 ppm
ATEmix (inhalation-dust/mist)	99,999.00 mg/l
ATEmix (inhalation-vapour)	99,999.00 mg/l

### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum gases, liquefied <0.1% w/w 1,3 Butadiene	-	-	LD50 (4h) >20 mg/l (rattus)
Acetone	=5800 mg/kg (Rattus) 3000 mg/Kg (mouse)	>15800 mg/Kg (Rattus)	=79 mg/l(Rattus) 4 h
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	LD50 >5840 mg/kg Rattus	LD50 >2920 mg/kg (Rattus)	LC50 >23.3 mg/L (4h)(Rat, vapour) (OECD 403)
Hydrocarbons, C6, isoalkanes, <5% n-hexane	>16750 mg/Kg (Rattus)	>3350 mg/Kg (Oryctolagus cuniculus) OECD 402	259354 mg/m <sup>3</sup> (vapour) (rat OECD 403)

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Classification based on data available for ingredients. Irritating to skin.

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Irritant. Read-across

**Serious eye damage/eye irritation** Classification based on data available for ingredients. Causes serious eye irritation.

Acetone (67-64-1)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye			irritant

**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

Acetone (67-64-1)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	Not a skin sensitiser

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	Did not cause sensitisation on laboratory animals

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET

OB41 Fast Tack Contact Adhesive Spray  
Date: 15.04.2024

Replaces: N/A  
Ref: 0634.0.AFT/DL

## Component Information

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)

Method	Species	Results
OECD Test No. 471: Bacterial Reverse Mutation Test	Salmonella typhimurium, in vitro	Not mutagenic in AMES Test

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as mutagenic.

Chemical name	European Union
Petroleum gases, liquefied <0.1% w/w 1,3 Butadiene	Muta. 1B

**Carcinogenicity** Based on available data, the classification criteria are not met.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	European Union
Petroleum gases, liquefied <0.1% w/w 1,3 Butadiene	Carc. 1A

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT - single exposure** May cause drowsiness or dizziness.

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** May be fatal if swallowed and enters airways.

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

### 11.2.2. Other information

**Other adverse effects** No information available.

## SECTION 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity** Toxic to aquatic life with long lasting effects. Harmful to aquatic life.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Acetone 67-64-1	-	LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss)	EC50 = 14500 mg/L 15 min	EC50 48 h 10294 - 17704 mg/L (Daphnia magna Static)		
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	ErL50 (72h) = 10-30 mg/L (Pseudokirchneriella subcapitata)	LL50 (96h) >13.4 mg/L (Oncorhynchus mykiss) OECD 203	-	EL50 (48h) = 3.0 mg/L (Daphnia magna)	1	1

# SAFETY DATA SHEET

OB41 Fast Tack Contact Adhesive Spray  
Date: 15.04.2024

Replaces: N/A  
Ref: 0634.0.AFT/DL

Hydrocarbons, C6, isoalkanes, <5% n-hexane 64742-49-0	EL50 (72h) = 13.6 mg/l (Pseudokirchneriella subcapitata)	LL50 (96h) = 18.27 mg/l (Oncorhynchus mykiss)	-	EL50 (48h)= 31.9 mg/l (Daphnia magna)		
--	--	---	---	---	--	--

## 12.2. Persistence and degradability

**Persistence and degradability** No information available.

Acetone (67-64-1)

Method	Exposure time	Value	Results
OECD Test No. 301B: Ready Biodegradability: CO2 Evolution Test (TG 301 B)	28 days	biodegradation	91 % Readily biodegradable

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	98%	Readily biodegradable

## 12.3. Bioaccumulative potential

**Bioaccumulation**

### Component Information

Chemical name	Partition coefficient
Petroleum gases, liquefied <0.1% w/w 1,3 Butadiene	2.8
Acetone	-0.24
Hydrocarbons, C6, isoalkanes, <5% n-hexane	3.6

## 12.4. Mobility in soil

**Mobility in soil** No information available.

## 12.5. Results of PBT and vPvB assessment

**PBT and vPvB assessment** The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
Petroleum gases, liquefied <0.1% w/w 1,3 Butadiene	The substance is not PBT / vPvB
Acetone	The substance is not PBT / vPvB PBT assessment does not apply
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	The substance is not PBT / vPvB
Hydrocarbons, C6, isoalkanes, <5% n-hexane	The substance is not PBT / vPvB

## 12.6. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

## 12.7. Other adverse effects

No information available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

# SAFETY DATA SHEET

OB41 Fast Tack Contact Adhesive Spray  
Date: 15.04.2024

Replaces: N/A  
Ref: 0634.0.AFT/DL

<b>Waste from residues/unused products</b>	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
<b>Contaminated packaging</b>	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.
<b>European Waste Catalogue</b>	16 05 04* gases in pressure containers (including halons) containing dangerous substances 15 01 04 metallic packaging
<b>Other information</b>	Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

### Land transport (ADR/RID)

14.1 UN number or ID number	UN1950
14.2 Proper Shipping Name	Aerosols
14.3 Transport hazard class(es)	2
Labels	2.1
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, 2, (D), Environmentally Hazardous
14.5 Environmental hazards	Yes
14.6 Special Provisions	190, 327, 344, 625
Classification code	5F
Tunnel restriction code	(D)
Limited quantity (LQ)	1 L

### IMDG

14.1 UN number or ID number	UN1950
14.2 Proper Shipping Name	Aerosols
14.3 Transport hazard class(es)	2.1
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, 2.1, Marine Pollutant
14.5 Marine pollutant	P
14.6 Special Provisions	63,190, 277, 327, 344, 381, 959
Limited Quantity (LQ)	See SP277
EmS-No	F-D, S-U
14.7 Maritime transport in bulk according to IMO instruments	Not applicable

### Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	UN1950
14.2 Proper Shipping Name	Aerosols, flammable
14.3 Transport hazard class(es)	2.1
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, flammable, 2.1
14.5 Environmental hazards	Yes
14.6 Special Provisions	A145, A167, A802
Limited quantity (LQ)	30 kg G
ERG Code	10L

## Section 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

# SAFETY DATA SHEET

OB41 Fast Tack Contact Adhesive Spray  
Date: 15.04.2024

Replaces: N/A  
Ref: 0634.0.AFT/DL

## Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

### **SVHC: Substances of Very High Concern for Authorisation:**

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

### **EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction**

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH Annex XVII
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0	28. 29. 75.
Hydrocarbons, C6, isoalkanes, <5% n-hexane	64742-49-0	28. 29. 75.

### **Substance subject to authorisation per REACH Annex XIV**

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

### **Dangerous substance category per Seveso Directive (2012/18/EU)**

P3a - FLAMMABLE AEROSOLS

P3b - FLAMMABLE AEROSOLS

E2 - Hazardous to the Aquatic Environment in Category Chronic 2

### **Named dangerous substances per Seveso Directive (2012/18/EU)**

Chemical name	Lower-tier requirements (tons)	Upper-tier requirements (tons)
Petroleum gases, liquefied <0.1% w/w 1,3 Butadiene - 68476-85-7	50	200
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics - 64742-49-0		25000
Hydrocarbons, C6, isoalkanes, <5% n-hexane - 64742-49-0		25000

### **Ozone-depleting substances (ODS) regulation (EC) 1005/2009**

Not applicable

### **Persistent Organic Pollutants**

Not applicable

### **REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors**

This product contains

Chemical name	Reporting of suspicious transactions, disappearances and thefts	Restricted
Acetone - 67-64-1	X	

### **National regulations**

### **15.2. Chemical safety assessment**

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No

# SAFETY DATA SHEET

OB41 Fast Tack Contact Adhesive Spray  
Date: 15.04.2024

Replaces: N/A  
Ref: 0634.0.AFT/DL

Chemical Safety Assessment has been carried out for this mixture

## SECTION 16: Other information

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of H-Statements referred to under section 3

EUH066 - Repeated exposure may cause skin dryness or cracking  
H225 - Highly flammable liquid and vapour  
H304 - May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness  
H411 - Toxic to aquatic life with long lasting effects

#### Notes relating to the identification, classification and labelling of substances

**Note K:** The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w 1,3- butadiene (Einecs No 203-450-8), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P210-P403 shall apply

**Note P:** The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes.

Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 shall apply

**Note S:** This substance may not require a label according to Article 17 (see Section 1.3 of Annex I) (Table 3)

**Note U (Table 3):** When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned:

Press. Gas (Comp.)

Press. Gas (Liq.)

Press. Gas (Ref. Liq.)

Press. Gas (Diss.)

Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2)

#### Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
IATA	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

#### Key literature references and sources for data

No information available

**Prepared By** Product Safety & Regulatory Affairs

**Revision date** 16-Feb-2023

#### Indication of changes

# SAFETY DATA SHEET

OB41 Fast Tack Contact Adhesive Spray  
Date: 15.04.2024

Replaces: N/A  
Ref: 0634.0.AFT/DL

---

**Revision note** Not applicable.  
**Training Advice** No information available  
**Further information** No information available

## Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**