

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : DRY FLEX® 16 - Component B

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use
Use of the substance/mixture : Elastic repair compound
Product only to be used in combination with component A.

1.2.2. Uses advised against

No additional information available.

1.3. Details of the supplier of the safety data sheet

Repair Care International
Cartografenweg 34
5141 MT Waalwijk - Nederland
T + 31(0) 416 650095 - F + 31(0) 416 652024
info@repair-care.com - www.repair-care.com

1.4. Emergency telephone number

Country	Official advisory body	Address	Emergency number	Remark
United Kingdom	National Poisons Information Service (Belfast Centre) Royal Victoria Hospital	Grosvenor Road BT12 6BA Belfast	0344 892 0111	Only for the purpose of informing medical personnel in cases of acute intoxications

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4 H302
Skin corrosion/irritation, Category 1, Sub-Category 1B H314
Serious eye damage/eye irritation, Category 1 H318
Skin sensitisation, Category 1 H317
Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412
Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) :

Danger

Contains

: Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia; Amines, polyethylenepoly-, triethylenetetramine fraction; m-phenylenebis(methylamine); Cashew (Anacardium occidentale) Nutshell Extract, Decarboxylated, Distilled

Hazard statements (CLP) :

: H302 - Harmful if swallowed.
H314 - Causes severe skin burns and eye damage.
H317 - May cause an allergic skin reaction.
H412 - Harmful to aquatic life with long lasting effects.



Precautionary statements (CLP) :

: P261 - Avoid breathing vapours, mist.
P264 - Wash Hands and forearms thoroughly after handling.
P280 - Wear eye protection, protective gloves, protective clothing.
P303+P361+P353+P310 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.. Immediately call a doctor, a POISON CENTER.
P305+P351+P338+P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a

DRY FLEX® 16 - Component B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

	doctor, a POISON CENTER. P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
EUH-statements	: EUH071 - Corrosive to the respiratory tract.
Labelling according to: exemption for packages of a capacity of 125ml or less	
Hazard pictograms (CLP)	:   GHS05 GHS07
Signal word (CLP)	: Danger
Hazardous ingredients	: Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia; Amines, polyethylenepoly-, triethylenetetramine fraction; m-phenylenebis(methylamine); Cashew (Anacardium occidentale) Nutshell Extract, Decarboxylated, Distilled
Hazard statements (CLP)	: H314 - Causes severe skin burns and eye damage. H317 - May cause an allergic skin reaction. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P261 - Avoid breathing vapours, mist. P264 - Wash Hands and forearms thoroughly after handling. P280 - Wear eye protection, protective gloves, protective clothing. P303+P361+P353+P310 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.. Immediately call a doctor, a POISON CENTER. P305+P351+P338+P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor, a POISON CENTER. P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
EUH-statements	: EUH071 - Corrosive to the respiratory tract.

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	Conc. (% w/w)	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia	CAS-No.: 9046-10-0 EC-No.: 618-561-0 REACH-no: 01-2119557899-12	< 25	Skin Corr. 1C, H314 Aquatic Chronic 3, H412
m-phenylenebis(methylamine)	CAS-No.: 1477-55-0 EC-No.: 216-032-5 REACH-no: 01-2119480150-50	< 50	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Corr. 1B, H314 Skin Sens. 1B, H317 Aquatic Chronic 3, H412
Cashew (Anacardium occidentale) Nutshell Extract, Decarboxylated, Distilled	CAS-No.: 8007-24-7 EC-No.: 700-991-6 REACH-no: 01-2119502450-57	5 – 10	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317
2,4,6-tris(dimethylaminomethyl)phenol	CAS-No.: 90-72-2 EC-No.: 202-013-9 EC Index-No.: 603-069-00-0 REACH-no: 01-2119560597-27	< 10	Acute Tox. 4 (Oral), H302 Skin Corr. 1C, H314 Eye Dam. 1, H318
Amines, polyethylenepoly-, triethylenetetramine fraction	CAS-No.: 90640-67-8 EC-No.: 292-588-2 REACH-no: 01-2119487919-13	< 5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412

DRY FLEX® 16 - Component B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

Name	Product identifier	Conc. (% w/w)	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Bis[(dimethylamino)methyl]phenol	CAS-No.: 71074-89-0 EC-No.: 275-162-0	< 2,5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335

Comments : Without VOC (volatile organic compounds)

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: Take off immediately all contaminated clothing. Rinse skin with water/shower. Get immediate medical advice/attention.
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting without medical advice. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Burns. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Presents no particular fire or explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon oxides (CO, CO ₂).

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Provide adequate ventilation.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel. Avoid contact with skin and eyes. Do not breathe vapours, mist.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Do not allow to enter drains or water courses.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material. Sweep or shovel spills into appropriate container for disposal.

DRY FLEX® 16 - Component B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". Concerning disposal elimination after cleaning, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Provide good ventilation in process area to prevent formation of vapour. Do not breathe vapours, mist. Avoid contact with skin and eyes. Wear personal protective equipment. Concerning personal protective equipment to use, see section 8.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool well ventilated place. Keep container closed when not in use.

Incompatible products : acids.

Storage temperature : 10 – 30 °C

Heat and ignition sources : Keep away from heat and direct sunlight.

7.3. Specific end use(s)

No additional information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. National occupational exposure and biological limit values

No additional information available.

8.1.2. Recommended monitoring procedures

No additional information available.

8.1.3. Air contaminants formed

No additional information available.

8.1.4. DNEL and PNEC

No additional information available.

8.1.5. Control banding

No additional information available.

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Provide local exhaust or general room ventilation to minimize vapour concentrations. Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

protective clothing. Gloves. Protective goggles.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Protective goggles. DIN EN 166

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing. CEN : EN 340; EN 369; EN 465

Hand protection:

Wear suitable gloves resistant to chemical penetration. Chemical resistant gloves (according to European standard NF EN 374 or equivalent).

DRY FLEX® 16 - Component B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Gloves	Nitrile rubber (NBR), Polyvinylchloride (PVC)	6 (> 480 minutes)	≥0,11		EN ISO 374

8.2.2.3. Respiratory protection

Respiratory protection:

No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation. In case of inadequate ventilation wear respiratory protection. EN 143

8.2.2.4. Thermal hazards

No additional information available.

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Odour	: characteristic.
Odour threshold	: No data available.
pH	: No data available.
Relative evaporation rate (butylacetate=1)	: No data available.
Melting point	: < 0 °C
Freezing point	: No data available.
Boiling point	: > 100 °C
Flash point	: > 104 °C
Auto-ignition temperature	: No data available.
Decomposition temperature	: No data available.
Flammability (solid, gas)	: No data available.
Vapour pressure	: No data available.
Relative vapour density at 20 °C	: > 1
Relative density	: 1,04
Solubility	: In water, material is partially soluble.
Partition coefficient n-octanol/water (Log Pow)	: No data available.
Viscosity, kinematic	: No data available.
Viscosity, dynamic	: No data available.
Explosive properties	: No data available.
Oxidising properties	: No data available.
Explosive limits	: No data available.

9.2. Other information

No additional information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known.

10.4. Conditions to avoid

Avoid extremely high (> 50 °C) or low (<5 °C) temperatures. Keep away from heat and direct sunlight.

10.5. Incompatible materials

acids.

DRY FLEX® 16 - Component B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

10.6. Hazardous decomposition products

No additional information available.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

DRY FLEX® 16 - Component B

ATE oral	1487,069 mg/kg bodyweight
----------	---------------------------

m-phenylenebis(methylamine) (1477-55-0)

LD50 oral rat	930 mg/kg
LD50 dermal rat	> 3100 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	≈ 1,34 mg/l/4h
ATE oral	930 mg/kg bodyweight
ATE dust/mist	1,5 mg/l/4h

Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia (9046-10-0)

LD50 oral rat	2885 mg/kg
LD50 dermal rabbit	2980 mg/kg
LC50 Inhalation - Rat	> 0,74 mg/l
ATE oral	2885 mg/kg bodyweight
ATE dermal	2980 mg/kg bodyweight

2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)

ATE oral	500 mg/kg bodyweight
----------	----------------------

Bis[(dimethylamino)methyl]phenol (71074-89-0)

ATE oral	500 mg/kg bodyweight
ATE dermal	1100 mg/kg bodyweight

Amines, polyethylenepoly-, triethylenetetramine fraction (90640-67-8)

LD50 oral rat	1716 mg/kg
LD50 dermal rabbit	1465 mg/kg
ATE oral	1716 mg/kg bodyweight
ATE dermal	1465 mg/kg bodyweight

Cashew (Anacardium occidentale) Nutshell Extract, Decarboxylated, Distilled (8007-24-7)

ATE oral	500 mg/kg bodyweight
ATE dermal	1100 mg/kg bodyweight

Skin corrosion/irritation : Causes severe skin burns.
Serious eye damage/irritation : Causes serious eye damage.
Respiratory or skin sensitisation : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified

Bis[(dimethylamino)methyl]phenol (71074-89-0)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

DRY FLEX® 16 - Component B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

m-phenylenebis(methylamine) (1477-55-0)

LC50 - Fish [1]	87,6 mg/l (OECD 203; Oryzias latipes)
EC50 - Crustacea [1]	15,2 mg/l (OECD 202; Daphnia magna)
ErC50 algae	33,3 mg/l (OECD 201; Pseudokirchneriella subcapitata)
NOEC chronic crustacea	4,7 mg/l (OECD 211; Daphnia magna)
NOEC chronic algae	10,5 mg/l (OECD 201; Pseudokirchneriella subcapitata)
Threshold limit - Algae [1]	12 mg/l (EC50; 72 h)

Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia (9046-10-0)

LC50 - Fish [1]	> 15 mg/l (OECD 203; Oncorhynchus mykiss)
EC50 - Crustacea [1]	80 mg/l (OECD 202; Daphnia magna)
ErC50 algae	15 mg/l (OECD 201; Pseudokirchneriella subcapitata)

2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)

LC50 - Fish [1]	> 100 mg/l (OECD 203; Cyprinus carpio)
EC50 - Crustacea [1]	> 100 mg/l (OECD 202; Daphnia magna)
ErC50 algae	46,7 mg/l (OECD 201; Pseudokirchneriella subcapitata)
NOEC chronic algae	≈ 1,13 mg/l (OECD 201; Pseudokirchneriella subcapitata)

Amines, polyethylenepoly-, triethylenetetramine fraction (90640-67-8)

LC50 - Fish [1]	330 mg/l (Pimephales promelas)
EC50 - Crustacea [1]	31,1 mg/l (EU Method C.2; Daphnia magna)
ErC50 algae	20 mg/l (OECD 201; Pseudokirchneriella subcapitata)
NOEC chronic algae	< 2,5 mg/l (OECD 201; Pseudokirchneriella subcapitata)

12.2. Persistence and degradability

m-phenylenebis(methylamine) (1477-55-0)

Persistence and degradability	Not readily biodegradable.
-------------------------------	----------------------------

Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia (9046-10-0)

Persistence and degradability	Not readily biodegradable.
-------------------------------	----------------------------

2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)

Persistence and degradability	Not readily biodegradable.
-------------------------------	----------------------------

Amines, polyethylenepoly-, triethylenetetramine fraction (90640-67-8)

Persistence and degradability	Not readily biodegradable.
-------------------------------	----------------------------

Cashew (Anacardium occidentale) Nutshell Extract, Decarboxylated, Distilled (8007-24-7)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

12.3. Bioaccumulative potential

m-phenylenebis(methylamine) (1477-55-0)

BCF - Fish [1]	< 2,7 (BCF)
Partition coefficient n-octanol/water (Log Pow)	≈ 0,18 (25 °C; pH 10,3 - 10,4)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

DRY FLEX® 16 - Component B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia (9046-10-0)

Partition coefficient n-octanol/water (Log Pow) 1,34 (25 °C)

2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)

Partition coefficient n-octanol/water (Log Pow) 0,219 (21,5 °C)

12.4. Mobility in soil

No additional information available.

12.5. Results of PBT and vPvB assessment

DRY FLEX® 16 - Component B

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.






Additional information : Empty containers should be taken for recycle, recovery or waste in accordance with local regulation.

Ecology - waste materials : Avoid release to the environment.

European List of Waste (LoW) code : 08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN 2735	UN 2735	UN 2735	UN 2735	UN 2735
14.2. UN proper shipping name				
AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS : m-phenylenebis(methylamine))	AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS : m-phenylenebis(methylamine))	Amines, liquid, corrosive, n.o.s. (CONTAINS : m-phenylenebis(methylamine))	AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS : m-phenylenebis(methylamine))	AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS : m-phenylenebis(methylamine))
Transport document description				
UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS : m-phenylenebis(methylamine)), 8, II, (E)	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS : m-phenylenebis(methylamine)), 8, II	UN 2735 Amines, liquid, corrosive, n.o.s. (CONTAINS : m-phenylenebis(methylamine)), 8, II	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS : m-phenylenebis(methylamine)), 8, II	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS : m-phenylenebis(methylamine)), 8, II
14.3. Transport hazard class(es)				
8	8	8	8	8
				
14.4. Packing group				
II	II	II	II	II
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available.				

DRY FLEX® 16 - Component B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: C7
Special provisions (ADR)	: 274
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P001, IBC02
Mixed packing provisions (ADR)	: MP15
Portable tank and bulk container instructions (ADR)	: T11
Portable tank and bulk container special provisions (ADR)	: TP1, TP27
Tank code (ADR)	: L4BN
Vehicle for tank carriage	: AT
Transport category (ADR)	: 2
Hazard identification number (Kemler No.)	: 80
Orange plates	:



Tunnel restriction code (ADR)	: E
EAC code	: 2X
APP code	: B

Transport by sea

Special provisions (IMDG)	: 274
Limited quantities (IMDG)	: 1 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T11
Tank special provisions (IMDG)	: TP1, TP27
EmS-No. (Fire)	: F-A
EmS-No. (Spillage)	: S-B
Stowage category (IMDG)	: A
Segregation (IMDG)	: SGG18, SG35
Properties and observations (IMDG)	: Colourless to yellowish liquids or solutions with a pungent odour. Miscible with or soluble in water. When involved in a fire, evolve toxic gases. Corrosive to most metals, especially to copper and its alloys. Reacts violently with acids. Cause burns to skin, eyes and mucous membranes.
MFAG-No	: 153

Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y840
PCA limited quantity max net quantity (IATA)	: 0.5L
PCA packing instructions (IATA)	: 851
PCA max net quantity (IATA)	: 1L
CAO packing instructions (IATA)	: 855
CAO max net quantity (IATA)	: 30L
Special provisions (IATA)	: A3, A803
ERG code (IATA)	: 8L

Inland waterway transport

Classification code (ADN)	: C7
Special provisions (ADN)	: 274
Limited quantities (ADN)	: 1 L

DRY FLEX® 16 - Component B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

Excepted quantities (ADN) : E2
Equipment required (ADN) : PP, EP
Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID) : C7
Special provisions (RID) : 274
Limited quantities (RID) : 1L
Excepted quantities (RID) : E2
Packing instructions (RID) : P001, IBC02
Mixed packing provisions (RID) : MP15
Portable tank and bulk container instructions (RID) : T11
Portable tank and bulk container special provisions (RID) : TP1, TP27
Tank codes for RID tanks (RID) : L4BN
Transport category (RID) : 2
Colis express (express parcels) (RID) : CE6
Hazard identification number (RID) : 80

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

EU restriction list (REACH Annex XVII)

Reference code	Applicable on	Entry title or description
3(b)	DRY FLEX® 16 - Component B ; Bis[(dimethylamino)methyl]phenol ; 2,4,6-tris(dimethylaminomethyl)phenol ; Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia ; Amines, polyethylenepoly-, triethylenetetramine fraction ; m-phenylenebis(methylamine) ; Cashew (Anacardium occidentale) Nutshell Extract, Decarboxylated, Distilled	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	DRY FLEX® 16 - Component B ; Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia ; Amines, polyethylenepoly-, triethylenetetramine fraction ; m-phenylenebis(methylamine)	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

DRY FLEX® 16 - Component B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

15.1.2. National regulations

No additional information available.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes

Section	Changed item	Change	Comments
	SDS EU format	Modified	
	Supersedes	Modified	
	Revision date	Modified	
2.1	Adverse physicochemical, human health and environmental effects	Modified	
2.1	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Modified	
2.2	Precautionary statements (CLP)	Modified	
2.2	Hazard pictograms (CLP)	Modified	
2.2	Hazard statements (CLP)	Modified	
3	Composition/information on ingredients	Modified	
4.1	First-aid measures after ingestion	Modified	
4.1	First-aid measures after eye contact	Modified	
4.1	First-aid measures after skin contact	Modified	
4.2	Symptoms/effects after eye contact	Added	
4.2	Symptoms/effects after ingestion	Added	
4.2	Symptoms/effects after skin contact	Modified	
5.2	Fire hazard	Modified	
5.2	Hazardous decomposition products in case of fire	Modified	
6.1	Emergency procedures	Modified	
7.1	Precautions for safe handling	Modified	
7.2	Storage conditions	Modified	
7.2	Storage temperature	Modified	
9.1	Relative vapour density at 20 °C	Modified	
9.1	Relative density	Modified	
9.1	Flash point	Modified	
11.1	ATE oral	Modified	
12.1	Ecology - general	Modified	
14.4	Packing group (IMDG)	Modified	
14.4	Packing group (ADN)	Modified	
14.4	Packing group (IATA)	Modified	
14.4	Packing group (ADR)	Modified	
14.6	Packing instructions (IMDG)	Modified	
14.6	Transport category (ADR)	Modified	
14.6	Excepted quantities (ADR)	Modified	
14.6	Limited quantities (ADR)	Modified	
16	Data sources	Modified	

DRY FLEX® 16 - Component B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

Abbreviations and acronyms	
SDS	Safety Data Sheet
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
PBT	Persistent Bioaccumulative Toxic
vPvB	Very Persistent and Very Bioaccumulative
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
LC50	Median lethal concentration
LD50	Median lethal dose
CAS	CAS (Chemical Abstracts Service) number
EG-nr	EINECS- en ELINCS-number
EINECS	European Inventory of Existing Commercial Substances
OEL	Occupational Exposure Limit

Data sources

: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878.

Other information

: REACH Disclaimer:

This information is based on current knowledge. Consistency of data in the SDS with CSR is considered, as far as the information is available at the time of compilation (cfr Revision date and Version number). **DISCLAIMER OF LIABILITY** The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

Full text of H- and EUH-statements	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Corr. 1C	Skin corrosion/irritation, Category 1, Sub-Category 1C
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
Skin Sens. 1B	Skin sensitisation, category 1B
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.

DRY FLEX® 16 - Component B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

Full text of H- and EUH-statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

Acute Tox. 4 (Oral)	H302	Calculation method
Skin Corr. 1B	H314	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 3	H412	Calculation method

Safety Data Sheet applicable for regions : GB - United Kingdom

The classification complies with : ATP 12