

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Bonda G4 Damp Seal
Product code : BON1218-
Type of product : Paint
Product group : End product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Professional use
Use of the substance/mixture : 55/999 Others
Function or use category : 55/999 Others

1.2.2. Uses advised against

Restrictions on use : Adhesives, sealants

1.3. Details of the supplier of the safety data sheet

Manufacturer

Bondaglass Voss Ltd
Rustins Ltd
Waterloo road
NW2 7TX London
United Kingdom
T +44 (0)208 450 4666 - F +44 (0)208 452 2008
rustins@rustins.co.uk - rustins.ltd

Distributor

Excellence Ltd
43 Grange Parade,
Unit 43 Baldoyle Industrial Estate,
D13 Y860 Dublin
Ireland
T 00353 (0)1 8323300 - F 00353 (0)1 8323584
Orders@excellence.ie - www.excellence.ie

1.4. Emergency telephone number

Emergency number : +44 (0)208 450 4666
OFFICE HOURS ONLY MON. - FRI. 08:00 - 16:30

| Country | Organisation/Company | Address | Emergency number | Comment |
|----------------|--|-----------------------------------|--|--------------------------------------|
| Ireland | National Poisons Information Centre Beaumont Hospital | PO Box 1297 Beaumont Road 9 | +353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7) | |
| United Kingdom | National Poisons Information Service (Birmingham Centre) City Hospital | Dudley Road B18 7QH | 0344 892 0111 | Only for healthcare professionals |

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226
Acute toxicity (inhalation:dust,mist) Category 4 H332
Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Respiratory sensitisation, Category 1 H334
Skin sensitisation, Category 1 H317
Germ cell mutagenicity, Category 1B H340

Bonda G4 Damp Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

| | |
|--|------|
| Carcinogenicity, Category 1B | H350 |
| Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation | H335 |
| Specific target organ toxicity – Repeated exposure, Category 2 | H373 |
| Hazardous to the aquatic environment – Chronic Hazard, Category 3 | H412 |

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness. Harmful if inhaled. May cause respiratory irritation. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

Contains

Hazard statements (CLP)

Precautionary statements (CLP)

- : Danger
- : Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).]; Prepolymer based on aromatic polyisocyanate
- : H226 - Flammable liquid and vapour.
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H332 - Harmful if inhaled.
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 - May cause respiratory irritation.
H340 - May cause genetic defects.
H350 - May cause cancer.
H373 - May cause damage to organs through prolonged or repeated exposure (if swallowed, if inhaled).
H412 - Harmful to aquatic life with long lasting effects.
- : P102 - Keep out of reach of children.
P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P241 - Use explosion-proof electrical/ventilating/lighting equipment.
P260 - Do not breathe vapours, fume.
P264 - Wash hands, forearms and face thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear eye protection, face protection.
P284 - Wear respiratory protection.
P302+P352 - IF ON SKIN: Wash with plenty of soap and water.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - IF exposed or concerned: Get medical advice/attention.
P312 - Call a POISON CENTER if you feel unwell.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

Bonda G4 Damp Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

| | |
|----------------|---|
| | P337+P313 - If eye irritation persists: Get medical advice/attention. |
| | P342+P311 - If experiencing respiratory symptoms: Call a POISON CENTER. |
| | P362+P364 - Take off contaminated clothing and wash it before reuse. |
| EUH-statements | : EUH204 - Contains isocyanates. May produce an allergic reaction. |
| Extra phrases | : As from 24 August 2023 adequate training is required before industrial or professional use. |

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|--|--|------------------|---|
| Prepolymer based on aromatic polyisocyanate | CAS-No.: 26447-40-5 | $\geq 50 - < 55$ | Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373 Aquatic Chronic 3, H412 |
| Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).] | CAS-No.: 64742-95-6 EC-No.: 265-199-0 EC Index-No.: 649-356-00-4 REACH-no: 01-2119455851-35 | $\geq 45 - < 50$ | Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304 |

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|---------------------------------------|--|
| First-aid measures general | : IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell. |
| First-aid measures after inhalation | : Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell. |
| First-aid measures after skin contact | : Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention. |
| First-aid measures after eye contact | : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. |
| First-aid measures after ingestion | : Call a poison center or a doctor if you feel unwell. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|-------------------------------------|--|
| Symptoms/effects | : May cause drowsiness or dizziness. |
| Symptoms/effects after inhalation | : May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| Symptoms/effects after skin contact | : Irritation. May cause an allergic skin reaction. |

Bonda G4 Damp Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

Symptoms/effects after eye contact : Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.
Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

Bonda G4 Damp Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.
Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

| Bonda G4 Damp Seal | |
|--|--|
| Austria - Occupational Exposure Limits | |
| Local name | Diphenylmethan-diisocyanat (Methylendiphenyldiisocyanat) (alle Isomeren): Diphenylmethan-4,4'-diisocyanat (MDI) |
| MAK (OEL TWA) | 0.05 mg/m ³ |
| MAK (OEL TWA) [ppm] | 0.005 ppm |
| MAK (OEL STEL) | 0.1 mg/m ³ (8x 5(Mow) min) |
| MAK (OEL STEL) [ppm] | 0.01 ppm (8x 5(Mow) min) |
| Remark | Sah. Krebs erzeugend: III B |
| Regulatory reference | BGBl. II Nr. 156/2021 |
| Belgium - Occupational Exposure Limits | |
| Local name | 4,4'-Diisocyanate de diphenylmethane (MDI) # Difenylmethaan-4,4'-di-isocyanat (MDI) |
| OEL TWA | 0.052 mg/m ³ |
| OEL TWA [ppm] | 0.005 ppm |
| Regulatory reference | Koninklijk besluit/Arrêté royal 11/05/2021 |
| Czech Republic - Occupational Exposure Limits | |
| Local name | Difenylmethan-4,4'-diisokyanát (1,1'-Methylenbis(4-isokyanatobenzen)) |
| PEL (OEL TWA) | 0.05 mg/m ³ |
| NPK-P (OEL C) | 0.1 mg/m ³ |
| Remark | I - dráždí sliznice (oči, dýchací cesty), respektive kůže, S - látka má senzibilizující účinek (s větou H317, H334). |
| Regulatory reference | Nařízení vlády č. 361/2007 Sb. (Předpis 195/2021 Sb.) |
| Denmark - Occupational Exposure Limits | |
| Local name | Diphenylmethan-4,4'-diisocyanat (MDI; Methylenbis(phenylisocyanat)) |
| OEL TWA [1] | 0.05 mg/m ³ |
| OEL TWA [2] | 0.005 ppm |
| Remark | K (betyder, at stoffet anses for at kunne være kræftfremkaldende) |
| Regulatory reference | BEK nr 202 af 21/02/2023 |
| Estonia - Occupational Exposure Limits | |
| Local name | 4,4'-metüleendifenüül-diisotsüanaat (fenüülisotsüanaat) |
| OEL TWA | 0.05 mg/m ³ |

Bonda G4 Damp Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

| Bonda G4 Damp Seal | |
|---|--|
| OEL TWA [ppm] | 0.005 ppm |
| OEL STEL | 0.1 mg/m ³ arvutatud 5-minutisele kokkupuuteajale |
| OEL STEL [ppm] | 0.01 ppm arvutatud 5-minutisele kokkupuuteajale |
| Remark | S (Sensibiliseeriv aine) |
| Regulatory reference | Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 21.12.2022, 3) |
| France - Occupational Exposure Limits | |
| Local name | 4,4'-Diisocyanate de diphénylméthane |
| VME (OEL TWA) | 0.1 mg/m ³ |
| VME (OEL TWA) [ppm] | 0.01 ppm |
| VLE (OEL C/STEL) | 0.2 mg/m ³ |
| VLE (OEL C/STEL) [ppm] | 0.02 ppm |
| Remark | Valeurs recommandées/admises; certaines ou toutes ces VLE s'entendent pour des concentrations mesurées sur une durée de 5 min; risque d'allergie respiratoire, substance classée cancérigène de catégorie 2 |
| Regulatory reference | Circulaire du Ministère du travail (réf.: INRS ED 984, 2016) |
| Germany - Occupational Exposure Limits (TRGS 900) | |
| Local name | 4,4'-Methylendiphenyldiisocyanat |
| AGW (OEL TWA) [1] | 0.05 mg/m ³ (E) |
| Peak exposure limitation factor | 1;=2=(I) |
| Remark | DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); 11 - Summe aus Dampf und Aerosolen; 12 - Der Arbeitsplatzgrenzwert gilt in der Regel nur für die Monomeren. Zur Beurteilung von Oligomeren oder Polymeren siehe TRGS 430 "Isocyanate"; H - hautresorptiv; Sah - Atemwegs- und Hautsensibilisierender Stoff; Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden |
| Regulatory reference | TRGS900 |
| Greece - Occupational Exposure Limits | |
| Local name | Δισοκυανικός εστέρας του διφαινυλομεθάνιου (MDI) |
| OEL TWA | 0.2 mg/m ³ |
| OEL TWA [ppm] | 0.02 ppm |
| OEL STEL | 0.2 mg/m ³ |
| OEL STEL [ppm] | 0.02 ppm |
| Regulatory reference | Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους |
| Hungary - Occupational Exposure Limits | |
| Local name | difenilmetán-4,4'-diizocianát (MDI) |
| AK (OEL TWA) | 0.05 mg/m ³ |
| CK (OEL STEL) | 0.05 mg/m ³ |

Bonda G4 Damp Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

| Bonda G4 Damp Seal | |
|--|--|
| Remark | i (ingerlő anyag, amely izgatja a bőrt, nyálkahártyát, szemet vagy mindhármat), sz (Túlérzékenységet okozó (szenzibilizáló) tulajdonságú anyag. Az anyagra érzékeny egyének „túlérzékenységen” alapuló bőr-, légzőrendszeri, esetleg más szervet/szervrendszert károsító megbetegedést okozhat); T (Azok az anyagok, amelyek egészségkárosító hatása TARTÓS expozíciót követően jelentkezik) |
| Regulatory reference | 5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről |
| Hungary - Biological Exposure Indices | |
| Local name | 4,4' Metilén difenil diizocianát (MDI) |
| BEI | 0.01 mg/l Biológiai expozíciós (hatás) mutató: 4,4' diaminodifenil-metán [MDA] (hidrolízis után) - Biológiai minta: vizeletben - Mintavétel ideje: m.v. (műszak végén) 0.05 µmol/l Biológiai expozíciós (hatás) mutató: 4,4' diaminodifenil-metán [MDA] (hidrolízis után) - Biológiai minta: vizeletben - Mintavétel ideje: m.v. (műszak végén) |
| Regulatory reference | 5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről |
| Ireland - Occupational Exposure Limits | |
| Local name | 4,4'-Methylene-diphenyl diisocyanate (as —NCO) [MDI] |
| OEL TWA [2] | 0.005 ppm |
| Remark | Sens. (In the workplace respiratory or dermal exposures to sensitising agents may occur. Sensitizers may evoke respiratory or dermal reactions, e.g. asthma, rhinitis and allergic contact dermatitis. The notation does not distinguish between respiratory or dermal sensitisation. Chemical agents that are sensitizers present special problems in the workplace. Should an employee become sensitised, subsequent exposure may cause intense responses, even at low exposure concentrations well below the OELV. Exposure should be eliminated or significantly reduced through control measures such as engineering and process controls and use of personal protective equipment (PPE)) |
| Regulatory reference | Chemical Agents Code of Practice 2021 |
| Lithuania - Occupational Exposure Limits | |
| Local name | Metileno bisfenilizocianatas (MDI) |
| IPRV (OEL TWA) | 0.05 mg/m ³ |
| IPRV (OEL TWA) [ppm] | 0.005 ppm |
| NRV (OEL C) | 0.1 mg/m ³ Nustatytas 5 min. poveikio trukmės NRD |
| NRV (OEL C) [ppm] | 0.01 ppm Nustatytas 5 min. poveikio trukmės NRD |
| Remark | J (jautrinantis poveikis); Tas pats RD, išreikštas ppm, taikomas izocianatams, kurių RD nenustatytas. Ši nuostata taikoma ir dulkių ar lašelių (aerozolių) pavidalo izocianatams, įskaitant prepolimerizuotus izocianatus (aduktus). Skirtingų medžiagų RD, išreikšti mg/m ³ , yra skirtingi. |
| Regulatory reference | LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12) |
| Poland - Occupational Exposure Limits | |
| Local name | Metylenobis(fenylizocyanian) (diizocyanian 4,4'-metylenodifenylu) |
| NDS (OEL TWA) | 0.03 mg/m ³ |
| NDSCh (OEL STEL) | 0.09 mg/m ³ |
| Regulatory reference | Dz. U. 2018 poz. 1286 |
| Portugal - Occupational Exposure Limits | |
| Local name | Metilendifenilisocianato (MDI) |
| OEL TWA [ppm] | 0.005 ppm |

Bonda G4 Damp Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

| Bonda G4 Damp Seal | |
|--|--|
| Regulatory reference | Norma Portuguesa NP 1796:2014 |
| Romania - Occupational Exposure Limits | |
| Local name | 4,4'-Metilendifenil diizocianat |
| OEL STEL | 0.15 mg/m ³ |
| Remark | C2 - susceptibil de a provoca apariția cancerului |
| Regulatory reference | Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 53/2021) |
| Slovakia - Occupational Exposure Limits | |
| Local name | Izokyanáty: 4,4'-Metyléndifenyilizokyanát (MDI) |
| NPHV (OEL TWA) [1] | 0.03 mg/m ³ |
| NPHV (OEL TWA) [2] | 0.002 ppm |
| Remark | S - znamená, že faktor môže spôsobiť senzibilizáciu |
| Regulatory reference | Nariadenie vlády č. 355/2006 Z. z. (236/2020 Z. z.) |
| Slovenia - Occupational Exposure Limits | |
| Local name | difenilmetan-4,4'-diizocianat (4,4'-metilendifenil diizocianat) |
| OEL TWA | 0.05 mg/m ³ 0.005 mg/m ³ |
| OEL STEL | 0.05 mg/m ³ |
| OEL STEL [ppm] | 0.005 ppm |
| Remark | K (Lastnost lažjega prehajanja snovi v organizem skozi kožo), Y (Snovi, pri katerih ni nevarnosti za zarodek ob upoštevanju mejnih vrednosti in BAT vrednosti) |
| Regulatory reference | Uradni list RS, št. 72/2021 z dne 11.5.2021 |
| Spain - Occupational Exposure Limits | |
| Local name | Diisocianato de 4,4'-difenilmetano (MDI) |
| VLA-ED (OEL TWA) [1] | 0.052 mg/m ³ |
| VLA-ED (OEL TWA) [2] | 0.005 ppm |
| Remark | Sen (Sensibilizante), r (Esta sustancia tiene establecidas restricciones a la fabricación, la comercialización o el uso en los términos especificados en el "Reglamento (CE) nº 1907/2006 sobre Registro, Evaluación, Autorización y Restricción de sustancias y preparados químicos" (REACH) de 18 de diciembre de 2006 (DOUE L 369 de 30 de diciembre de 2006). Las restricciones de una sustancia pueden aplicarse a todos los usos o sólo a usos concretos. El anexo XVII del Reglamento REACH contiene la lista de todas las sustancias restringidas y especifica los usos que se han restringido). |
| Regulatory reference | Límites de Exposición Profesional para Agentes Químicos en España 2023. INSHT |
| Sweden - Occupational Exposure Limits | |
| Local name | 4,4'-Metylendifenyldiisocyanat (MDI) |
| NGV (OEL TWA) | 0.03 mg/m ³ |
| NGV (OEL TWA) [ppm] | 0.002 ppm |
| KTV (OEL STEL) | 0.05 mg/m ³ |
| KTV (OEL STEL) [ppm] | 0.005 ppm |

Bonda G4 Damp Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

| Bonda G4 Damp Seal | |
|--|--|
| Remark | M (Medicinska kontroller kan krävas för hantering av ämnet. Se vidare föreskrifterna om medicinska kontroller i arbetslivet. För vissa ämnen ska arbetsgivaren erbjuda läkarundersökning och för andra ämnen gäller krav på periodisk läkarundersökning och tjänstbarhetsbedömning); S (Ämnet är sensibiliserande. Sensibiliserande ämnen kan ge allergi eller annan överkänslighet. Överkänslighetsbesvären drabbar främst huden eller andningsorganen. Överkänslighet innebär att man reagerar vid kontakt med ämnen som normalt inte ger besvär. Allergi är en undergrupp av överkänslighet som orsakas av reaktioner i kroppens immunsystem. Särskilt låga gränsvärden har fastställts för ämnen med mer uttalat luftvägssensibiliserande egenskaper. Några ämnen med starkt sensibiliserande egenskaper får endast hanteras efter tillstånd från Arbetsmiljöverket, se föreskrifterna om kemiska arbetsmiljörisiker. Dessa ämnen har inga gränsvärden men i vissa fall riktvärden); 2 (Korttidsgränsvärde som avser 5-minutersperiod gäller för ammoniak, diisocyanater, 2,6-diisopropylfenylisocyanat, fenylisocyanat, isocyanasyra och metylisocyanat. Korttidsgränsvärde som avser 1-minuters-period gäller för akrylsyra) |
| Regulatory reference | Hygieniska gränsvärden (AFS 2018:1) |
| Iceland - Occupational Exposure Limits | |
| Local name | Metýlenbis(fenýlísósýanat) (dífenýlmetan-4,4'-díísósýanat, MDI) |
| OEL TWA | 0.05 mg/m ³ |
| OEL TWA [ppm] | 0.005 ppm |
| OEL STEL | 0.1 mg/m ³ Þakgildið er miðað við fimm mínútna tímabil |
| OEL STEL [ppm] | 0.01 ppm Þakgildið er miðað við fimm mínútna tímabil |
| Remark | O (efnið er ofnæmisvaldandi) |
| Regulatory reference | Reglugerð um mengunarmörk og aðgerðir til að draga úr mengun á vinnustöðum (Nr. 390/2009) |
| Norway - Occupational Exposure Limits | |
| Local name | Difenylnmetan-4,4'-diisocyanat (MDI; Metylen-bis-fenylidiisocyanat) |
| Grenseverdi (OEL TWA) [1] | 0.05 mg/m ³ |
| Grenseverdi (OEL TWA) [2] | 0.005 ppm |
| Korttidsverdi (OEL STEL) [ppm] | 0.01 ppm |
| Remark | A: Kjemikalier som skal betraktes som at de fremkaller allergi eller annen overfølsomhet i øynene eller luftveier, eller som skal betraktes som at de fremkaller allergi ved hudkontakt. |
| Regulatory reference | FOR-2021-06-28-2248 |
| North Macedonia - Occupational Exposure Limits | |
| Local name | дифенилметан-4,4'-диизоцианат (4,4'-метилендифенил диизоцианат) |
| OEL TWA | 0.05 mg/m ³ |
| KTV | 1 |
| Short time value [mg/m ³] | 0.05 mg/m ³ |
| Remark | (KTV) краткотрајна вредност (КТВ) значи концентрација на опасни хемиски супстанции во воздухот на работното место внатре во зона на дишење, на која работникот без опасност по здравјето може да е изложен на покусо време. Изложеноста на краткотрајни вредности може да трае највеќе 15 минути и не смее да се повтори повеќе од четирипати во работната смена, при што меѓу две изложености на оваа концентрација мора да измине најмалку 60 минути. Краткотрајната вредност е изразена во mg/m ³ или во ml/m ³ (ppm) а е дадена како многукратни дозволени пречекорувања на граничната вредност |

Bonda G4 Damp Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

Bonda G4 Damp Seal

Regulatory reference

Правилник за минималните барања за безбедност и здравје при работа на вработени од ризици поврзани со изложување на хемиски супстанции („Службен весник на Република Македонија“ бр.46/10)

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Protective clothing. Dust/aerosol mask with filter type P1.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Colour : brown.
Odour : Characteristic odour.

Bonda G4 Damp Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

| | |
|---|--------------------------------|
| Odour threshold | : No data available |
| pH | : 7 |
| Relative evaporation rate (butylacetate=1) | : No data available |
| Melting point | : No data available. |
| Freezing point | : No data available |
| Boiling point | : No data available |
| Flash point | : 43 °C |
| Auto-ignition temperature | : No data available. |
| Decomposition temperature | : No data available |
| Flammability (solid, gas) | : Not applicable |
| Vapour pressure | : No data available |
| Relative vapour density at 20°C | : No data available. |
| Relative density | : No data available. |
| Solubility | : Material insoluble in water. |
| Partition coefficient n-octanol/water (Log Pow) | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| Explosive properties | : No data available |
| Oxidising properties | : No data available |
| Explosive limits | : No data available |

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

| | |
|-----------------------------|-----------------------|
| Acute toxicity (oral) | : Not classified |
| Acute toxicity (dermal) | : Not classified |
| Acute toxicity (inhalation) | : Harmful if inhaled. |

Bonda G4 Damp Seal

| | |
|---------------------------|------------------------------------|
| ATE CLP (dust,mist) | 3 mg/l/4h |
| Skin corrosion/irritation | : Causes skin irritation. pH: 7 |

Bonda G4 Damp Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

| | |
|-----------------------------------|---|
| Serious eye damage/irritation | : Causes serious eye irritation. pH: 7 |
| Respiratory or skin sensitisation | : May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. |
| Germ cell mutagenicity | : May cause genetic defects. |
| Carcinogenicity | : May cause cancer. |
| Reproductive toxicity | : Not classified |
| STOT-single exposure | : May cause respiratory irritation. |

Prepolymer based on aromatic polyisocyanate (26447-40-5)

| | |
|------------------------|---|
| STOT-single exposure | May cause respiratory irritation. |
| STOT-repeated exposure | : May cause damage to organs through prolonged or repeated exposure (if swallowed, if inhaled). |

Prepolymer based on aromatic polyisocyanate (26447-40-5)

| | |
|------------------------|--|
| STOT-repeated exposure | May cause damage to organs through prolonged or repeated exposure. |
| Aspiration hazard | : Not classified |

SECTION 12: Ecological information

12.1. Toxicity

| | |
|---|--|
| Ecology - general | : Toxic to aquatic life with long lasting effects. |
| Hazardous to the aquatic environment, short-term (acute) | : Not classified |
| Hazardous to the aquatic environment, long-term (chronic) | : Harmful to aquatic life with long lasting effects. |
| Not rapidly degradable | |

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

| | |
|-------------------------|---|
| Waste treatment methods | : Dispose of contents/container in accordance with licensed collector's sorting instructions. |
| Additional information | : Flammable vapours may accumulate in the container. |






SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

Bonda G4 Damp Seal

Safety Data Sheet


according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

| ADR | IMDG | IATA | ADN | RID |
|---|---|---|---|---|
| 14.1. UN number | | | | |
| UN 1263 | UN 1263 | UN 1263 | UN 1263 | UN 1263 |
| 14.2. UN proper shipping name | | | | |
| PAINT RELATED MATERIAL | PAINT RELATED MATERIAL | Paint | PAINT RELATED MATERIAL | PAINT RELATED MATERIAL |
| Transport document description | | | | |
| UN 1263 PAINT RELATED MATERIAL, 3, III, (D/E) | UN 1263 PAINT RELATED MATERIAL, 3, III | UN 1263 Paint, 3, III | UN 1263 PAINT RELATED MATERIAL, 3, III | UN 1263 PAINT RELATED MATERIAL, 3, III |
| 14.3. Transport hazard class(es) | | | | |
| 3 | 3 | 3 | 3 | 3 |
|  |  |  |  |  |
| 14.4. Packing group | | | | |
| III | III | III | III | III |
| 14.5. Environmental hazards | | | | |
| Dangerous for the environment: No | Dangerous for the environment: No Marine pollutant: No | Dangerous for the environment: No | Dangerous for the environment: No | Dangerous for the environment: No |
| No supplementary information available | | | | |

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1
 Special provisions (ADR) : 163, 367, 650
 Limited quantities (ADR) : 5I
 Excepted quantities (ADR) : E1
 Packing instructions (ADR) : P001, IBC03, LP01, R001
 Special packing provisions (ADR) : PP1
 Mixed packing provisions (ADR) : MP19
 Portable tank and bulk container instructions (ADR) : T2
 Portable tank and bulk container special provisions (ADR) : TP1, TP29
 Tank code (ADR) : LGBF
 Vehicle for tank carriage : FL
 Transport category (ADR) : 3
 Special provisions for carriage - Packages (ADR) : V12
 Special provisions for carriage - Operation (ADR) : S2
 Hazard identification number (Kemler No.) : 30
 Orange plates :



Tunnel restriction code (ADR) : D/E
 EAC code : •3Y

Transport by sea

Special provisions (IMDG) : 163, 223, 367, 955
 Limited quantities (IMDG) : 5 L
 Excepted quantities (IMDG) : E1

Bonda G4 Damp Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

| | |
|------------------------------------|--|
| Packing instructions (IMDG) | : P001, LP01 |
| Special packing provisions (IMDG) | : PP1 |
| IBC packing instructions (IMDG) | : IBC03 |
| Tank instructions (IMDG) | : T2 |
| Tank special provisions (IMDG) | : TP1, TP29 |
| EmS-No. (Fire) | : F-E |
| EmS-No. (Spillage) | : S-E |
| Stowage category (IMDG) | : A |
| Properties and observations (IMDG) | : Miscibility with water depends upon the composition. |

Air transport

| | |
|--|-----------------|
| PCA Excepted quantities (IATA) | : E1 |
| PCA Limited quantities (IATA) | : Y344 |
| PCA limited quantity max net quantity (IATA) | : 10L |
| PCA packing instructions (IATA) | : 355 |
| PCA max net quantity (IATA) | : 60L |
| CAO packing instructions (IATA) | : 366 |
| CAO max net quantity (IATA) | : 220L |
| Special provisions (IATA) | : A3, A72, A192 |
| ERG code (IATA) | : 3L |

Inland waterway transport

| | |
|-----------------------------------|-----------------|
| Classification code (ADN) | : F1 |
| Special provisions (ADN) | : 163, 367, 650 |
| Limited quantities (ADN) | : 5 L |
| Excepted quantities (ADN) | : E1 |
| Equipment required (ADN) | : PP, EX, A |
| Ventilation (ADN) | : VE01 |
| Number of blue cones/lights (ADN) | : 0 |

Rail transport

| | |
|---|---------------------------|
| Classification code (RID) | : F1 |
| Special provisions (RID) | : 163, 367, 650 |
| Limited quantities (RID) | : 5L |
| Excepted quantities (RID) | : E1 |
| Packing instructions (RID) | : P001, IBC03, LP01, R001 |
| Special packing provisions (RID) | : PP1 |
| Mixed packing provisions (RID) | : MP19 |
| Portable tank and bulk container instructions (RID) | : T2 |
| Portable tank and bulk container special provisions (RID) | : TP1, TP29 |
| Tank codes for RID tanks (RID) | : LGBF |
| Transport category (RID) | : 3 |
| Special provisions for carriage – Packages (RID) | : W12 |
| Colis express (express parcels) (RID) | : CE4 |
| Hazard identification number (RID) | : 30 |

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

Bonda G4 Damp Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

Organic solvent : Yes

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

France

| Occupational diseases | |
|-----------------------|---|
| Code | Description |
| RG 84 | Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide |

Germany

- Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG).
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).
- Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1).
- Chemicals Prohibition Ordinance (ChemVerbotsV) : This product is subject to ChemVerbotsV Annex 2 Entry 1. The following requirements must be observed: authorization requirement (according to § 6 paragraph 1 sentence 1), basic requirements for carrying out the delivery (according to § 8 paragraph 1, 3 and 4), identification and documentation (according to § 9 paragraph 1 to 3) and exclusion of the shipping route (according to § 10).
- Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

- ABM category : Z(1) - non biodegradable substances with hazardous properties for humans and the environment (carcinogenicity/ mutagenicity/ reprotoxicity/bioaccumulative potential/ toxicity or persistence)
- SZW-lijst van kankerverwekkende stoffen : Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).] is listed
- SZW-lijst van mutagene stoffen : Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).] is listed
- SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
- SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed

Bonda G4 Damp Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

Class for fire hazard : Class II-1
Store unit : 5 liter
Classification remarks : R10 <H226;H315;H317;H319;H332;H334;H335;H340;H350;H373;H412>; Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product
Persons suffering from asthma or eczema and persons who have chronic lung diseases, skin or respiratory allergies to isocyanates should not work with the material
The requirements from the Danish Working Environment Authorities regarding work with epoxy resins and isocyanates must be observed during use and disposal
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

Switzerland

Storage class (LK) : LK 3 - Flammable liquids
Chemicals Ordinance (SR 813.11) : Group 1

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

| Abbreviations and acronyms: | |
|-----------------------------|---|
| ADN | European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways |
| ADR | European Agreement concerning the International Carriage of Dangerous Goods by Road |
| ATE | Acute Toxicity Estimate |
| BCF | Bioconcentration factor |
| BLV | Biological limit value |
| BOD | Biochemical oxygen demand (BOD) |
| COD | Chemical oxygen demand (COD) |
| DMEL | Derived Minimal Effect level |
| DNEL | Derived-No Effect Level |
| EC-No. | European Community number |
| EC50 | Median effective concentration |
| EN | European Standard |
| IARC | International Agency for Research on Cancer |
| IATA | International Air Transport Association |
| IMDG | International Maritime Dangerous Goods |
| LC50 | Median lethal concentration |
| LD50 | Median lethal dose |
| LOAEL | Lowest Observed Adverse Effect Level |
| NOAEC | No-Observed Adverse Effect Concentration |
| NOAEL | No-Observed Adverse Effect Level |
| NOEC | No-Observed Effect Concentration |
| OECD | Organisation for Economic Co-operation and Development |

Bonda G4 Damp Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

| Abbreviations and acronyms: | |
|-----------------------------|--|
| OEL | Occupational Exposure Limit |
| PBT | Persistent Bioaccumulative Toxic |
| PNEC | Predicted No-Effect Concentration |
| RID | Regulations concerning the International Carriage of Dangerous Goods by Rail |
| SDS | Safety Data Sheet |
| STP | Sewage treatment plant |
| ThOD | Theoretical oxygen demand (ThOD) |
| TLM | Median Tolerance Limit |
| VOC | Volatile Organic Compounds |
| CAS-No. | Chemical Abstract Service number |
| N.O.S. | Not Otherwise Specified |
| vPvB | Very Persistent and Very Bioaccumulative |
| ED | Endocrine disrupting properties |

| Full text of H- and EUH-statements: | |
|-------------------------------------|--|
| Acute Tox. 4 (Inhalation) | Acute toxicity (inhal.), Category 4 |
| Aquatic Chronic 3 | Hazardous to the aquatic environment – Chronic Hazard, Category 3 |
| Asp. Tox. 1 | Aspiration hazard, Category 1 |
| Carc. 1B | Carcinogenicity, Category 1B |
| Carc. 2 | Carcinogenicity, Category 2 |
| EUH204 | Contains isocyanates. May produce an allergic reaction. |
| Eye Irrit. 2 | Serious eye damage/eye irritation, Category 2 |
| H226 | Flammable liquid and vapour. |
| H304 | May be fatal if swallowed and enters airways. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |
| H332 | Harmful if inhaled. |
| H334 | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| H335 | May cause respiratory irritation. |
| H340 | May cause genetic defects. |
| H350 | May cause cancer. |
| H351 | Suspected of causing cancer. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H412 | Harmful to aquatic life with long lasting effects. |
| Muta. 1B | Germ cell mutagenicity, Category 1B |
| Resp. Sens. 1 | Respiratory sensitisation, Category 1 |
| Skin Irrit. 2 | Skin corrosion/irritation, Category 2 |
| Skin Sens. 1 | Skin sensitisation, Category 1 |

Bonda G4 Damp Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

Full text of H- and EUH-statements:

| | |
|-----------|--|
| STOT RE 2 | Specific target organ toxicity – Repeated exposure, Category 2 |
| STOT SE 3 | Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation |

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.