



Waterloo Road, London NW2 7TX. Tel: +44 (0)20 8450 4666 www.bondaglass.com

October 2018

PRODUCT DATA SHEET

Product	Bonda Rust Primer & Zinc
Type	Modified alkyd resin with anti-corrosive additives
Intended Use	An anti-rust primer that is used to stop further corrosion and allow a paintable surface after drying, on most metals, including automotive use.
Special Features	Low viscosity material that can be used in a spray gun without thinning and high penetration for superior corrosion protection
Preparation	Expose the rusted area fully, to effectively tackle the corrosion from spreading further and remove any oils or grease from the area. Repair any dents, holes before application.
Application	Can be applied with a brush, roller or spray gun. The material does not need the use of thinners, due to its low viscosity, use cellulose thinners to thin product.
Coats	2 coats maximum
Drying Time	4 hours
Re-coating Time	The second coat can be applied straight after the first coat is touch dry
Application Temp.	Can be applied in poor weather conditions, high humidity and temperatures down to 0°C
Coverage	7sq. metres per litre
Maintenance	Non-Applicable
Compatibility	Compatible under most synthetic, household, cellulose, enamel, oil-based, and two component paints, but check suitability before use.
Settlement	Stir well before use for any possibility of settlement
Shelf-life/Storage	18 months if stored under the recommended conditions. Store in cool and dry place below 25 deg C
Hazards	Flammable. Keep out of reach of children. Use only in well ventilated areas. Keep away from sources of ignition – no smoking. Avoid contact with skin and eyes. After contact with skin, wash immediately with plenty of soap and water or a proprietary skin cleanser. Do not use White Spirit. A full Safety Data Sheet is available upon request or on www.rustins.co.uk
Clean-Up	All tools must be cleaned immediately after use with Rustins Cellulose Thinners before product sets hard.
Sizes	2.5L