

Dryzone® Mould-Resistant Emulsion Paint

Product Description

Dryzone® Mould-Resistant Emulsion Paint is a premium quality, low odour mould-resistant interior coating designed to protect against unsightly and unhygienic black mould even when there is persistent condensation. The performance of **Dryzone® Mould-Resistant Emulsion Paint** is achieved by combining modern paint technology with advanced paint-film protection. It is fully washable and resistant to the effects of condensation when the coating is fully dried out. Ideal for walls and ceilings in private and social housing and a wide range of public and commercial buildings.

Benefits

- Prevents the recurrence of black mould for up to 5 years
- Quick drying
- Compatible with all known undercoat paint finishes
- Easy to use and cost effective

Properties

Appearance	Available in 2 different colours:
	<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="background-color: #e0e0e0; padding: 5px; border: 1px solid #ccc;">Brilliant White</div> <div style="background-color: #fff9c4; padding: 5px; border: 1px solid #ccc;">Magnolia</div> </div>
Size(s) & Packaging	1 litre and 5 litre tubs
Coverage	10 – 12 m ² per litre
Service Life	5 years
Storage	Store above 5 °C in dry conditions. Keep container tightly closed and away from children
Shelf Life	12 months
Thinning	Use clean tap water but do not exceed 10% by volume



Application Information

Preparation


Preparation is straightforward and very similar to normal good decorative practice.

1. Put down dust sheets before work begins
2. Remove any loose material such as old paint, grease, dirt, mould or defective wallpaper
3. If mould is present, thoroughly clean the area using Dryzone® 100 Mould Sanitiser. Avoid sanding the mould area to reduce spreading of spores.
4. Allow to dry thoroughly.
5. For glossy surfaces lightly abrade the surface with abrasive paper avoiding inhalation of dust and wearing suitable personal protective equipment (face mask, gloves, safety spectacles etc).
6. If necessary, apply an appropriate primer or sealer. For new or porous plaster surfaces use **Dryzone® Mould-Resistant Emulsion Paint** thinned up to 10 % with clean tap water as normal good practice. Allow to dry thoroughly. New plasterwork should be allowed to dry for 7 – 14 days before applying any paint finish.

Application

Apply **Dryzone® Mould-Resistant Emulsion Paint** using brush or roller.

1. Ensure the area is well ventilated. Stir thoroughly before use.
2. Apply two coats of **Dryzone® Mould-Resistant Emulsion Paint**. Allow the first coat to dry fully before applying the second coat.
3. Each coat will typically be touch dry after 2 – 4 hours depending on temperature, humidity and airflow.
4. The surface temperature during application should be between 10 – 25°C
5. Clean equipment with clean tap water before the paint dries.
- 6 **Dryzone® Mould-Resistant Emulsion Paint** should not be covered with any other paint or wallpaper.



Other Information

Dryzone® Mould-Resistant Emulsion Paint will help compliance with Section 82 (Statutory Nuisance), Chapter 43 of the Environmental Protection Act 1990, either used alone or part of various strategies to prevent condensation and mould growth in both private and public tenanted accommodation.

For more information see the Safety Datasheet (SDS).

Information given is in good faith based on experience and usage, however all recommendations are made without warranty or guarantee, since the conditions of use are beyond our control. All goods are sold in accordance with our Conditions of Sale, copies of which are available on request. Customers are advised that products, techniques and codes of practice are under constant review and changes occur without notice; please ensure you have the latest updated information.