

PRODUCT DATA SHEET

EVERBUILD® 408 Super Seal

HIGH PERFORMANCE SOLVENT BASED WATER REPELLENT

PRODUCT DESCRIPTION

EVERBUILD® 408 Super Seal is a spirit based transparent water repellent, formulated to prevent attack by water penetration on brick, stone, concrete, plaster, rendering etc. EVERBUILD® 408 Super Seal penetrates deep into the treated area to provide effective repellency for many years. Dries clear. Can be applied by spray, brush or roller.

USES

As an effective water repellent on:

- Brick
- Stone
- Render
- Masonry
- Pebbledashing.

CHARACTERISTICS / ADVANTAGES

- Improved durability and beading effect.
- Solvent based, quick drying formula.
- Works on most common mineral surfaces.
- Deep penetrating formula for lasting protection.
- Dries clear - colourless.
- Allows surface to breathe
- Can be applied by brush, roller or low pressure spray.

Active Components Siloxane resin/solvent blend.

Application Temperature +5 - 40°C, do not apply where surface temp. exceeds 40°C

PRODUCT INFORMATION

Packaging	5ltr metal tin
Appearance / Colour	Clear liquid
Shelf Life	12 months from date of manufacture.
Storage Conditions	Store between 5 and 25°C in dry conditions.
Density	0.88 - 0.92 g/cm ³

APPLICATION INFORMATION

Consumption Coverage will vary depending on the porosity of the substrate. As a quick guide, brick coverage will be approx. 5 sq. metres per litre for the first coat, 8 sq. metres per litre for the second coat.

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

All surfaces must be clean and sound, free from dirt, mould, algae, grease and other contamination. Carry out surface repairs and fill cracks before application.

APPLICATION

Shake can well before use. Apply by low pressure spray, brush or roller.

NOTE: THIS PRODUCT WILL DRY CLEAR.

On vertical surfaces, saturate the wall working from the bottom up, ensuring the entire surface is covered. On horizontal surfaces, flood the entire area then after 10 minutes, spread out with a soft brush, roller or mop to ensure the entire area is covered.

Two coats are normally required; the second coat being applied within 1 hour – as soon as the first coat has soaked in and whilst the surface is still wet. Clean brushes, rollers and spray equipment with white spirits IMMEDIATELY after use.

DRYING TIME – Approx. 1-2 hours; depending on air temperature.

LIMITATIONS

- Do not apply to damp/wet surfaces.
- Do not apply when raining or when rain is imminent.
- Do not use on non porous surfaces.
- Do not use on wood, plastic or rubber.
- Do not use in fishponds.
- Protect windows and surrounding areas from overspray. Remove any overspray immediately whilst the product is still wet, with a cloth .

Note: The surface to be treated may darken after the first application. Always test a small area first PRIOR to coating the whole surface

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

Consult MSDS for full list of hazards.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

EVERBUILD BUILDING PRODUCTS LTD

Site 41, Knowsthorpe Way
Cross Green Industrial Estate
Leeds, LS9 0SW
Tel: 0113 240 3456
Web: www.everbuild.co.uk
Twitter: @everbuild

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @SikaIreland

EVERBUILD408SuperSeal-en-GBEVER-(02-2018)-1-1.pdf

Product Data Sheet
EVERBUILD® 408 Super Seal
February 2018, Version 01.01
020405030010000088