

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Roof & Gutter Sealant

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Consumer use, Professional use
Use of the substance/mixture : adhesives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

Soudal N.V.
Everdongenlaan 18-20
2300 Turnhout
Belgium
T +32 14 42 42 31, F +32 14 42 65 14
sds@soudal.com, www.Soudal.com

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Belgium	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Militaire Reine Astrid	Rue Bruyn 1 1120 Brussels	+32 70 245 245	Please dial: 070 245 245 for any urgent questions about intoxication (free of charge 24/7), if not accessible, dial: 02 264 96 30 (standard fee)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226
Specific target organ toxicity – Single exposure, Category 3, H336
Narcosis

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour. May cause drowsiness or dizziness.

Roof & Gutter Sealant

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

Signal word (CLP) :

Warning

Contains :

n-butyl acetate

Hazard statements (CLP) :

H226 - Flammable liquid and vapour.

H336 - May cause drowsiness or dizziness.

Precautionary statements (CLP) :

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P261 - Avoid breathing vapours.

P271 - Use only outdoors or in a well-ventilated area.

P312 - Call a POISON CENTER, a doctor if you feel unwell.

P405 - Store locked up.

P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

EUH-statements :

EUH066 - Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

The product does not meet the PBT and vPvB classification criteria

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Component	
white mineral oil (petroleum) (8042-47-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
n-butyl acetate (123-86-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
n-butyl acetate substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1 REACH-no: 01-2119485493-29	$\geq 25 - < 50$	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066

Roof & Gutter Sealant

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
white mineral oil (petroleum) substance with national workplace exposure limit(s) (BE)	CAS-No.: 8042-47-5 EC-No.: 232-455-8 REACH-no: 01-2119487078-27	≥ 5 – < 10	Not classified

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
------------------	--------------------------------------

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: None known.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing vapours, mist.
----------------------	--

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

6.2. Environmental precautions

Avoid release to the environment.

Roof & Gutter Sealant

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Cover spill with non combustible material, e.g.: sand/earth. Shovel or sweep up and put in a closed container for disposal. Clean contaminated surfaces with an excess of water. Wash clothing and equipment after handling. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
- Incompatible products : Heat sources. Ignition sources.
- Maximum storage period : ≈ 1 year
- Packaging materials : Synthetic material.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

white mineral oil (petroleum) (8042-47-5)	
Belgium - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
OEL STEL	10 mg/m ³
n-butyl acetate (123-86-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	241 mg/m ³
	50 ppm
IOEL STEL	723 mg/m ³
	150 ppm
Belgium - Occupational Exposure Limits	
OEL TWA	238 mg/m ³

Roof & Gutter Sealant

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

n-butyl acetate (123-86-4)	
	50 ppm
OEL STEL	712 mg/m ³
	150 ppm

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

n-butyl acetate (123-86-4)	
DNEL/DMEL (Workers)	
Acute - systemic effects, dermal	11 mg/kg bw/day
Acute - systemic effects, inhalation	600 mg/m ³
Acute - local effects, inhalation	600 mg/m ³
Long-term - systemic effects, dermal	11 mg/kg bw/day
Long-term - systemic effects, inhalation	300 mg/m ³
Long-term - local effects, inhalation	300 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, dermal	6 mg/kg bw/day
Acute - systemic effects, inhalation	300 mg/m ³
Acute - systemic effects, oral	2 mg/kg bw/day
Acute - local effects, inhalation	300 mg/m ³
Long-term - systemic effects, oral	2 mg/kg bw/day
Long-term - systemic effects, inhalation	35,7 mg/m ³
Long-term - systemic effects, dermal	6 mg/kg bw/day
Long-term - local effects, inhalation	35,7 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	0,18 mg/l
PNEC aqua (marine water)	0,018 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0,981 mg/kg dwt
PNEC sediment (marine water)	0,098 mg/kg dwt
PNEC (Soil)	
PNEC soil	0,09 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	35,6 mg/l

8.1.5. Control banding

No additional information available

Roof & Gutter Sealant

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses (EN 166)

8.2.2.2. Skin protection

Skin and body protection:

Protective clothing (EN 14605 or EN 13034)

Hand protection:

Protective gloves against chemicals (EN 374)

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Transparent. white. brown. Grey.
Appearance	: Viscous liquid.
Odour	: solvent-like.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not applicable
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 23 – 60 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 0,95 kg/l (20°C)

Roof & Gutter Sealant

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Relative density : Not available
Relative vapour density at 20°C : Not available
Particle characteristics : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : ≈ 39 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Ignition sources. Heat sources.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

white mineral oil (petroleum) (8042-47-5)	
LD50 oral rat	> 5000 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Read-across, Oral, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg bodyweight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Read-across, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 5 mg/l (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Read-across, Inhalation (aerosol), 14 day(s))
n-butyl acetate (123-86-4)	
LD50 oral rat	10760 – 12789 mg/kg bodyweight (Equivalent or similar to OECD 423, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 14112 mg/kg bodyweight (Equivalent or similar to OECD 402, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	0,74 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))

Roof & Gutter Sealant

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Skin corrosion/irritation : Not classified

white mineral oil (petroleum) (8042-47-5)	
pH	No data available in the literature

n-butyl acetate (123-86-4)	
pH	6,2 (0.53 %, 20 °C)

Serious eye damage/irritation : Not classified

white mineral oil (petroleum) (8042-47-5)	
pH	No data available in the literature

n-butyl acetate (123-86-4)	
pH	6,2 (0.53 %, 20 °C)

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : May cause drowsiness or dizziness.

n-butyl acetate (123-86-4)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

white mineral oil (petroleum) (8042-47-5)	
Viscosity, kinematic	> 20,5 mm ² /s (40 °C)

n-butyl acetate (123-86-4)	
Viscosity, kinematic	0,831 mm ² /s (20 °C, ASTM D445: Capillary viscometer)

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Not rapidly degradable

white mineral oil (petroleum) (8042-47-5)	
LC50 - Fish [1]	> 100 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)

n-butyl acetate (123-86-4)	
LC50 - Fish [1]	18 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)

EC50 - Crustacea [1]	44 mg/l (Equivalent or similar to OECD 202, 48 h, Daphnia sp., Static system, Fresh water, Experimental value, Locomotor effect)
----------------------	--

Roof & Gutter Sealant

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

n-butyl acetate (123-86-4)	
ErC50 algae	397 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Read-across, GLP)

12.2. Persistence and degradability

white mineral oil (petroleum) (8042-47-5)	
Persistence and degradability	Not readily biodegradable in water.

n-butyl acetate (123-86-4)	
Persistence and degradability	Readily biodegradable in water.
ThOD	2,21 g O ₂ /g substance

12.3. Bioaccumulative potential

white mineral oil (petroleum) (8042-47-5)	
BCF - Other aquatic organisms [1]	1216 l/kg (BCFBAF v3.01, Estimated value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	5,18 (Experimental value)
Bioaccumulative potential	Potential for bioaccumulation (500 ≤ BCF ≤ 5000).

n-butyl acetate (123-86-4)	
Partition coefficient n-octanol/water (Log Pow)	2,3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

white mineral oil (petroleum) (8042-47-5)	
Surface tension	No data available in the literature, Data waiving
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2,64 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Low potential for adsorption in soil.

n-butyl acetate (123-86-4)	
Surface tension	61,3 mN/m (20 °C, 0.1 %, OECD 115: Surface Tension of Aqueous Solutions)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1,268 – 1,844 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

12.5. Results of PBT and vPvB assessment

Roof & Gutter Sealant	
The product does not meet the PBT and vPvB classification criteria	
Component	
white mineral oil (petroleum) (8042-47-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
n-butyl acetate (123-86-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

Roof & Gutter Sealant

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available



SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Do not discharge into drains or the environment.
Additional information	: Flammable vapours may accumulate in the container.
Ecological information	: Avoid release to the environment.
European List of Waste (LoW, EC 2000/532)	: 08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances 15 01 10* - packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not regulated	UN 1133	UN 1133	Not regulated	Not regulated
14.2. UN proper shipping name				
Not regulated	ADHESIVES	Adhesives	Not regulated	Not regulated
Transport document description				
Not regulated	UN 1133 ADHESIVES, 3, III (23°C c.c.)	UN 1133 Adhesives, 3, III	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	3	3	Not regulated	Not regulated
Not regulated			Not regulated	Not regulated
14.4. Packing group				
Not regulated	III	III	Not regulated	Not regulated
14.5. Environmental hazards				
Not regulated	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Not regulated	Not regulated
No supplementary information available				

14.6. Special precautions for user

Special transport precautions	: Transport in accordance with section 2.2.3.1.5 of the ADR (viscous substance) may be applied, Transport in accordance with section 2.2.3.1.5 of the ADN (viscous substance) may be applied, Transport in accordance with section 2.2.3.1.5 of the RID (viscous substance) may be applied
-------------------------------	--

Roof & Gutter Sealant

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Overland transport

Not regulated

Transport by sea

Special provisions (IMDG)	: 223, 955
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T2
Tank special provisions (IMDG)	: TP1
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-D
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Adhesives are solutions of gums, resins, etc., usually volatile due to the solvents. Miscibility with water depends upon their composition.

Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3
ERG code (IATA)	: 3L

Inland waterway transport

Not regulated

Rail transport

Not regulated

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(a)	Roof & Gutter Sealant ; n-butyl acetate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	Roof & Gutter Sealant ; n-butyl acetate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10

Roof & Gutter Sealant

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
40.	n-butyl acetate	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

VOC content : $\approx 39\%$

Seveso Directive (Disaster Risk Reduction)

Seveso Additional information : P5C

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
	according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878		

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor

Roof & Gutter Sealant

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:	
EUH066	Repeated exposure may cause skin dryness or cracking.
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H336	May cause drowsiness or dizziness.
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Roof & Gutter Sealant

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Flam. Liq. 3	H226	On basis of test data
STOT SE 3	H336	Calculation method

Safety Data Sheet (SDS), EU-2023-1

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.